

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6, T.28-7½

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Pg. 5231)

Set post, standard cor. of Tp. T28 S., Rs. 7 and 8 W., from which:

A B.Oak 10" dia., bears S.8°W., 44 lks. dist.

A B.Oak 12" dia., bears S.61°E., 184 lks. dist.

GLO survey by Fred Mensch, under Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5853-54)

Intersect the cor. established by Hathorn for standard cor of T.28S Rs. 7 and 8 W., located by measurement from the original bearing trees. Old blaze on SE. tree has been opened and marks are plain. SW. tree is a decayed stump, old blazes visible. At the exact cor. point, Set an Iron post, 3 ft. long, 3" dia., 26" in the ground, for cor. of T.28S Rs. 7½ and 8 West., with brass cap marked:

S 1|S 6
R 8|R7½W
T28S
1924

from which (new Bearing trees)

A Fir 20" dia., bears S.29°E., 52 lks. dist., marked
T 28 S R 7½ W S 6 BT.

A Fir 20" dia., bears S.12°W., 47 lks. dist., marked
T 28 S R 8 S 1 BT.

Original bearing tree, a B.Oak 16" dia., bears S.62°E., (instead of S.61°E.) 184 lks. dist.

Stump of original bearing tree, a B.Oak 10" dia., bears S.3°W., (instead of S.8°W.) 44 lks. dist.

H.L. Eppstein, Co. Surveyor - June 1930 - M 1-73 - C.S. File 14/59

Standard Government Pipe.

Witness trees:

24" Red Fir S.30°30'E., 32.8 ft.

30" Red Fir S.11°W., 29.5 ft.

(Continued Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 109100

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6, T.28-7½

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Geisler, For: Champion International Corp. M 90-79
Nov. 1985-Jan. 1986

Found - 1924 GLO 3¼" brass cap on a 3" I.P.
23" rotted Fir stump, 3 ft. tall bears S.12°W.,
30.3 ft. (Rec. 31.0 ft.) No scribing.
25" rotted Fir stump bears S.29°E., 34.3 ft. No
scribing
New BTs -8" Fir bears S.6½°E., 136.0 ft. scribed T28S R7½W.,
S6 BT.
8" Fir bears S.31°W., 198.3 ft. scribed T28S
R8W S1 BT.