

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. ¼ Cor. Section 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - May 1, 1997 - C.S. 64/74-25

Mon. Fd.- 2½" dia. brass cap on a 1" OD iron pipe, protrudes
2" above ground. (1924)

Accessories Fd.-

15" now 23" dia. W.Oak, with a previously opened
unhealed rotted blaze, no scribing visible,
bears S.26°W., 13' (rec. S.26°W., 11.9' dist.
is a face measurement) OBT

15" now 25" dia. W.Oak, with a previously opened
unhealed rotted blaze, no scribing visible,
bears N.25°W., 13' (rec. N.25°W., 11.9' dist.
is a face measurement) OBT

24" now 26" dia. 1½' high oak stump, with a healed
blaze, bears S.56½°W., 47.3' (rec. S.56½°W.,
46.5' dist is a slope measurement) 1930 DCSO

8" now 9" dia. W.Oak, with a fully healed double
blaze, bears N.69°W., 44.3' (rec. N.67½°W.,
44.9' dist. is a slope measurement) 1961 DCSO

SE BT from 1930 DCSO ren now gone

NE BT from 1961 DCSO ren now gone

New Accessories -

10" dia. W.Oak, double blazed and scribed "¼ S31 CS
BT", bears N.16°W., 57.3'.

Corner lies at the intersection of a east and west and north
running fence corners.