

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 140240

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

H. C. Brown, Deputy Co. Surveyor - For: C. H. Allen Volume 2
Page 142 Sept. 1906

For center stake, drove into the ground, an Iron stake 1½"
dia. and 2½ ft. in length. Marked witness trees as follows:
A Fir 12" dia., bears N.25°E., 29 lks.
A Fir 12" dia., bears S.74°E., 20 lks.
A Fir 16" dia., bears S.46°W., 30 lks.
A Fir 16" dia., bears N.15°W., 40 lks.

Ken Hoffine - For: Lone Rock Timber Co. - 6/2002 - M 140-25

Set - 2½" alum. cap on 5/8" x 40" iron rod marked LONE ROCK
TIMBER T27S R7W C¼ S30 2002 PLS 2291
13" D.Fir bears S.67°W., 52.9 ft., we scribe C¼ S30 BT
& tag tree.
15" D.Fir bears S.17°E., 38.4 ft., we scribe C¼ S30 BT
& tag tree.
20" D.Fir bears N.16°W., 13.8 ft., we scribe C¼ S30 BT
& tag tree.
24" D.Fir bears N.70°E., 33.5 ft., we scribe C¼ S30 BT
& tag tree.
Corner sits on SE slope in mound of stones.