TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 147100

PRIMARY CORNER DESCRIPTION A.P. 1/4 Cor. Sec. 6 only, T28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5231)

Standard 1/4 sec. cor., from which
An Oak 20" dia., bears S.69°E., 52 lks. dist.
An Oak 10" dia., bears S.56°W., 57 lks. dist.

GLO survey by Mensch,1924 - (DCSO records, Vol. 14 Page 5852)

Intersect the cor. established by Hathorn for standard ¼ sec. cor. of sec. 6, located by measurement from the original BTs, both alive and standing. At the exact cor.point:
Set an iron post, 3 ft. long 1" dia., 28" in the ground, for angle point, with brass cap marked: A P
1924

from which (new bearing tree)
A W.Oak 20" dia.,bears N.41°E., 19 lks. dist. mkd. AP BT
A Fir 12" dia., bears N.61°W., 48 lks. dist. mkd. AP BT.
Original bearing tree, an Oak 28" dia., blazes open and marks plain, bears S.69°E., 52 lks. dist.
Orig. BT, an Oak 14" dia., bears S.57°W., (instead of S.56°W.) 57 lks. dist., showing old blazes.
A W.Oak 20" dia., county surveyor's new BT, erroneous restoration as 1/4 sec. cor. of sec. 6, bears N.65°E., 82 lks. dist., marked C S ¼ S 6 T28S R7W BT. (See Eppstein visit, Feb. 9, 1922, C.S. 7/40 & "old" corner book, Page 111 and Ford's 1/4 Cor. for Sec. 31, T.27-7 Vol. 14 Page 5222)
This corner has been used by county and local surveyors for partial subdivision of sec. 6.
Ford's standard 1/4 sec. cor. of sec. 6, bears N.34°33'E., 8.97 chs. dist.

Eppstein - for: Lane and Fitzpatrick - June 1930 - No record source found, see "old" corner book, page 111

A.P. on township line. Standard Gov't corner set by Mensch, 1924. Witness trees:
W.Oak 24" dia.,bears N.42°E.,12.3 ft.
Red Fir 10" dia., bears N.59°W., 31.1 ft.

Fd. Ok by D.Edwards, 11/96, M 126-13.