

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy under Contract dated April 12, 1855 (DCSO records, Vol. 13 Page 5262)

Set ¼ sec. post, from which
 A W.Oak 20" dia., bears N.75°W., 23 lks. dist.
 A W.Oak 10" dia., bears N.50°E., 55 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy M. Godfrey; S. Bilow - April 24, 1958 - C.S. File 49/79 (See also Brown survey, Vol. 2 Page 142)

Found - Orig. 10" now 14" W.Oak. I open old scar & find good scribing, "BT". This BT still partly alive.
 Orig. NW BT gone.
Set Brass cap at cor. mkd: S30|S29 T27S R7W County Surveyor Office, 1958
NW fence line is East 9.0 ft.
New BTs - 14" R.Fir bears N.45°E., 64.2 ft. scribed
 ¼ S29 CS BT.
 18" B.Oak bears S.32½°E., 33.4 ft. scribed ¼ S29 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/26/1999 - C.S. File 66/8-8

Found: 2½" dia. brass cap on a 1½" o.d. iron pipe, protrudes 12" above ground. 1958
 10" now 14" dia. dead W.Oak with a previously opened rotted blaze, bears N.50°E., 36.3 ft. 0BT
 18" now 21" dia. B.Oak with a fully healed double blaze, bears S.32½°E., 33.4 ft. 1958
 14" now 28" dia. D.Fir with a fully healed double blaze, bears N.45°E., 64.2 ft. 1958
New: 9" dia. D.Fir doubled blazed & scribed "¼ S30 CS BT" bears N.40°W., 6.0 ft.
 5" dia. madrone bark scribed "¼ S30 CS BT" bears S.39°W., 25.1 ft.
Corner lies 8 ft. west of a N-S fence line.

Found OK by T. Hostetter, July 2001 - M138-66
Fd. BC by Mark Heimburger, 5/2008 - M155-67