

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 13 Pages 5264)

Set 1/4 sec. post, from which
 A Fir 20" dia., bears N.33°W., 42 lks. dist.
 A Fir 8" dia., bears N.62°E., 29 lks. dist.

Don Garrett, For: Hayward Reed - Jan. 1, 1968 - M 33-27

Set by proportional measurement.
Set Brass cap stamped "1/4 Cor. S19, 20 T27S R7W LS 544.
BTs - 4" madrone bears N.69°W., 21.6 ft. scribed "1/4 S19 BT".
16" Cedar bears S.86°15'E., 140.7 ft. scribed "1/4 S20 BT"

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/9/1999 - C.S. File 66/8-29

Found: 2 1/2" brass cap on a 1 1/2" o.d. iron pipe protrudes 10" above ground. 1968
4" now 9" dia. Madrone with a fully healed single blaze, bears N.69°W., 21.6 ft. 1968
16" now 35" dia. cedar with a fully healed single blaze, bears S.86 1/4°E., 140.7 ft. 1968
New: 6" dia. cedar double blazed and scribed "1/4 S 19 CS BT" , bears S.63 1/2°W., 5.2 ft.
14" dia. Madrone bark scribed "1/4 S20 CS BT" bears S.56°E., 12.0 ft.
Note: Corner lies in a N-S fence line

Found OK by T. Hostetter, May 2000 - M135-4