

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. and L.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Vol. 13 Page 5272)

Set post, 3 ft. long, 4" sq. for 1/4 sec. cor., from which
A Fir 6" dia., bears N.20°E., 11 lks. dist.
A Cedar 10" dia., bears S.30°W., 20 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-70

Found - Both orig. BTs. Orig. 6", now down & mostly rotted
Fir, N.20°E., 7.3 ft. We find old scribe marks.
Orig. 10" now 11" Cedar snag, S.30°W., 13.2 ft.
Shows good scribing "1/4".
We find a 4"x4" stake & 1/2" I.P. bears S.13°W. 6.3 ft
Set Brass cap at cor. mkd: County Surveyors Office, 1960
1/4 S7|S8 T27S R7W
New BTs - 14" R.Cedar bears S.60 1/2°E. 21.2 ft scribed 1/4 S8 CSBT
16" R.Cedar bears S.42 1/2°W. 46.6 ft scribed 1/4 S7 CSBT

Tony Hostetter - For: Weyerhaeuser Co. - June 2002 - M140-54

Found - 1960 brass cap set by DCSO
22" Cedar, WEYCO tag, bears S.45°E.. 14.6 ft. to
center.
32" Fir stump, WEYCO tag, bears S.35°W., 20.0 ft. to
center.
New BTs - 15" Hemlock, scribed "S8 1/4 BT" bears S.42°53'E.,
24.4 ft. to spike.
14" Hemlock, scribed "S8 1/4 BT" bears S.8°E., 17.1
ft. spike.
14" Hemlock, scribed "S7 1/4 BT" bears S.78°51'W.,
18.3 ft. to spike.