

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - A.R. and L.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Vol. 13 Page 5272)

Set a Laurel post 3½ ft. long, 4" sq. firmly in the ground, from which:

- A Fir 36" dia., bears N.75°W., 6 lks. dist.
- A Fir 30" dia., bears N.50°E., 57 lks. dist.
- A Fir 36" dia., bears N.80°E., 75 lks. dist.
- A Fir 36" dia., bears S.30°W., 40 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-71

Found - All orig. BTs:
Orig. 36" now 40" R.Fir N.75°W., 4.0 ft., shows good bark scribing "T".
Orig. 30" now 48" R.Fir, (rec. N.50°E., 37.6 ft.) We find to be N.7°E., 30.0 ft., shows good bark scribing "W 1".
Orig. 36" now 42" R.Fir (Rec. S.30°W., 26.4 ft.) We find should be S.35°W., 15.6 ft., shows bark scribing "27".
Orig. 36" now 50" R.Fir S.80°E., 49.5 ft., we find should be S.80°E., 39.5 ft. shows old axe work.

BTs in this area do not check close for record bearings and distances. All scribing and axe work seems to be old and original. This section corner checks calls to East OK.

Set Brass cap at cor. mkd: County Surveyors $\frac{S 6}{S 7} | \frac{S 5}{S 8}$ T27S R7W Office, 1960

New BTs - 18" R.Fir bears N.54°E., 67.0 ft. scribed S5 T27S R7W CS BT.
Rescribed (bark) now 42" R.Fir S.35°W., 15.6 ft. S7 T27S R7W CS BT.
50" R.Fir S.79°E., 41.8 ft. S8 T27S R7W CS BT.
40" R.Fir N.75°W., 4.0 ft. S6 T27S R7W CS BT.

Tony Hostetter - For: Weyerhaeuser Co. - June 2002 - M140-54

Found - 1960 brass cap set by DCSO
18" Fir, mkd. by County Surveyor is now 20" stump 8' tall scribing visible (not measured)
50" Fir @ S.79°E., now a stump, scribe visible, BT tag (not measured)
42" Fir @ S.35°W., now a stump, bark scribing visible, BT (not measured)
40" Fir @ N.75°W., now a stump, scribing visible, BT tag (not measured) continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7, and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 15" Fir, scribed "S5 SW BT", bears N.68°30'E., 25.6 ft. to spike.
18" Fir, scribed "S8 NW BT", bears N.3°45'E., 10.0 ft. to spike.
13" Fir, scribed "S6 SE BT", bears N.6°16'W., 20.5 ft. to spike.

Ron Quimby - For: Weyerhaeuser - 6/2017 - M173-35

Found - Brass cap per 1960 renewal
18" Fir stump bears N.54°E., 67.0' - healed blaze
50" Fir stump bears S.79°E., 41.8' - healed blaze
42" Fir stump bears S.35°W., 15.6' - visible scribe
40" Fir stump bears N.75°W., 4.0' - visible scribe
24" Fir bears N.68°E., 25.6' (to spike in root collar) healed blaze
24" Fir bears S.4°E., 10.0' (to spike in root collar) healed blaze
19" Fir bears N.6°W., 20.5' (to spike in root collar) healed blaze
New BT - 14" Fir bears S.60°W., 8.7' - scribed 'T27S R7W S7 BT'