

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 232500

PRIMARY CORNER DESCRIPTION Witness Corner 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Tony Hostetter - For: Weyerhaeuser Co. - June 2002 - M140-54 ----- Witness corner: Bears S.89°42'05"W., 530.73 ft. from actual corner. Set - 5/8" x 30" rebar w/plastic cap mkd: "HOSTETTER LS 1975" 16" Fir, scribed "S8 WC BT" bears N.34°E., 7.3 ft. to spike. 30" Fir, scribed "S8 WC BT" bears N.84°W., 16.7 ft. to spike.</p>
<p>Carl Sweeden - For: Roseburg Resources Co. - Dec. 2006 - M151-78 ----- Found - 5/8" I.R. W/Y.P.C. "HOSTETTER LS 1975" up 0.4'. W.C. to N 1/4 corner due to steep rocky cliffs. 17" D.Fir BT, N.38°E., 7.4' (N.34°E., 7.3'), scar vis. & tag 30" D.Fir BT, N.84°W., 16.7', scar vis. & tag.</p>
<p>Fd. 5/8" rebar & 2 BTs by Ron Rice 3/2009 M158-80</p>
<p>Tony Hostetter - For: Weyerhaeuser Co. - Dec. 2022 - M181-66 ----- Fd. 5/8" IRs & BTs per M151-78</p>