TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 13 Pages 5264-65)

Set ¼ sec. post, from which
A B.Oak 15" dia., bears N.23°E., 172 lks. dist.
A W.Oak 30" dia., bears S.40°E., 132 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; S. Bilow - July 3, 1958 - C.S. File 49/79-54

Found - Orig. 15" now 36" B.Oak N.23°E., 113.5 ft. I open lower scar & find good scribing "BT" on partly rotted face.
No trace of orig. SE BT. Area south of line has been cultivated years ago, no old trees left.
Set Brass cap at cor. mkd: ¼ S17 / S20 T27S R7W County Surveyor's Office, 1958
New BTs - 10" B.Oak bears N.27°E., 21.2 ft. scribed ¼ S17 CS BT.
32" B.Oak bears S.73°W., 160.3 ft. scribed ¼ S20 CS BT.

Carl Sweeden - For: Roseburg Resources Co. - December 2006 - M151-78

Found - 2½" DCSO brass cap "1958", up 0.7' in open pasture depression in ground @ N.23°E., 113.0', no tree
No trace of B.Oak @ N.27°E. 21.2'
32" now 46" B.Oak BT, S.73°W., 160.3', faint healed blaze, tag added.
New BTs - 16" madrone BT N.15°E., 238.1' scribed "S ¼ S17 BT" tagged.
18" madrone BT N.62°E., 273.9' scribed "S ¼ S17 BT" tagged.
45" B.Oak BT, S.44°E., 338.0', scribed "S ¼ S17 BT" tagged.

Tony Hostetter - For: Weyerhaeuser Co. - Dec. 2022 - M181-66

Fd. BC & BTs per M151-78