

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - A.R. and L.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Vol. 13 Page 5270)

Set a post, 3½ ft. long and 4" sq. for ¼ sec. cor., from which

- A Fir, 8" dia., bears N.3°E., 56 lks.
- A Laurel, 5" dia., bears S.20°W., 7 lks.

Tony Hostetter - For: Weyerhaeuser Co. - June 2002 (Added 12/19/2022) - M140-54

Witness corner (bears S.89°42'05"W., 530.73 from computed corner point)

Set - 5/8"x30" rebar w/plastic cap marked HOSTETTER LS 1975 from which:

- 16" Fir, scribed "S8 WC BT" bears N.34°E., 7.3 ft to spike.
- 30" Fir, scribed "S8 WC BT" bears N.84°W., 16.7 ft to spike.

Carl Sweeden - For: Roseburg Resources Co. - Dec. 2006 (Added 12/19/2022) - M151-78

Condition report only

Found - 5/8" I.R. W/Y.P.C. "HOSTETTER LS 1975" up 0.4', WC to N¼ corner due to steep rocky cliffs.

17" D.Fir BT, N.38°E., 7.4' (N.34°E., 7.3') scar vis. & tag.

30" D.Fir BT, N.84°W., 16.7', scar vis. & tag.

Ron Rice - For: Seneca Jones Timber Co. & Roseburg Resources Co. - 3/2009 - M158-80

Set - 2½" aluminum cap on 5/8" x 24" rebar due to bedrock, flush with ground, mkd: T27S R7W

¼ $\frac{S8}{S17}$
2009
54633LS

26" D.Fir bears N.58½°W. 18.7' blazed scribed "¼ S8 BT"

9" D.Fir bears S.77½°E 8.0' blazed, scribed "¼ S17 BT"

3/8" x 3" "survey marker" spike with brass washer marked

"RM" set flush in rock outcrop bears S.26°04'15"W.,

31.30' Chiseled "B0 X" in vertical rock face 3" "X"

bears N.38°00'00"E., 4.02'