

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Secs. 5 & 8

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - A.R. and L.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Vol. 13 Page 5273)

Set a post, 3½ ft. long and 4" sq. for ¼ sec. cor., from which,

An Alder, 24" dia., bears S.20°E., 27 lks.

A Maple, 12" dia., bears N.35°W., 13 lks.

Tony Hostetter - For: Weyerhaeuser Co. - June 2002 - M140-54

Found no evidence of corner or accessories.

Set - 5/8" x 30" rebar w/plastic cap mkd: "HOSTETTER LS 1975"
14" Fir scribed "S5 ¼ BT" bears N.2°E., 11.3 ft. to spike.

18" Fir scribed "S8 ¼ BT" bears S.76°27'E., 26.1 ft. to spike.

18" Fir scribed "S8 ¼ BT" bears S.27°21'E., 22.7 ft. to spike.

20" Fir scribed "S8 ¼ BT" bears S.69°16'W., 1.7 ft. to spike.

Fd. 5/8" rebar & 4 BTs by Ron Rice 3/2009 M158-80

Ron Quimby - For: Weyerhaeuser - June 2017 - M173-35

Found - 5/8" iron rod with yellow plastic cap stamped "HOSTETTER LS 1925" per M140-54

16" Fir bears N.2°E., 11.3' (to spike in root collar) healed face

21" Fir bears S.76°E., 26.1' (to spike in root collar) healed face

24" Fir bears S.27°E., 22.7' (to spike in root collar) healed face

28" Fir bears S.69°W., 1.7' (to spike in root collar) healed face