TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 251100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5 only, T28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

1924 GLO survey by Mensch (DCSO records, Vol. 14 Page 5848)

Intersect center meridional subdivision line of original section 5. At this point
Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of resurvey sec. 5, with brass cap marked:

¼ S 5
1924

from which
A B.Oak 10" dia., bears S.66°E., 22 lks. dist., mkd. S5 BT.
A Fir 14" dia., bears S.36°W., 46 lks. dist., mkd. ¼ S5 BT.
Ford's original ¼ sec. cor. of sec. 5, restored as witness point, bears N.4°54'W., 4.41 chs. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-38

Found - 14" now 18" R.Fir S.36°W., 30.4 ft. shows good scars.
SE BT standing, but dead.
1924 brass cap at corner.
New BT - 20" R.Fir bears S.51°E., 12.5 ft. scribed ¼ S5 CSBT

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20001)

Fd. by Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/6/1998 - C.S. File 66/2-28