TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5225)

Set post, cor. secs. 32 and 33, from which
A B.Oak 8" dia., bears N.81°E., 118 lks. dist.
A Laurel 30" dia., bears N.65°W., 40 lks. dist.
(Corner set by Ford, bears North 339 lks. & East 248 lks.)

GLO survey by Fred Mensch, Under Contract #109 dated 1924 (DCSO records, Volume 14 Page 5847)

Intersect the cor. of secs. 32 and 33, located by record measurement from the original bearing trees. The NE tree is now a dead stub on which the scribe marks are legible. The NW tree in place and shows evidence of the blazes.
At the exact cor. point, Set an Iron post, 3 ft. long, 2" dia., 27" in the ground, for cor., with brass cap marked:

T27S:R7W
S32:S33 AP5
1924

from which
(new bearing tree) A Fir 16" dia., bears N.66°E., 28 lks. dist., mkd. T27S R7W S33 BT.
(Old bearing tree) A Laurel, 36" dia., bears N.65°W., 40 lks. dist., mkd. T27S R7W S32 BT.
The original NE bearing tree, an Oak stub 12" dia., bears N.81°E., 118 lks. dist.
(Cor. established by Ford for cor. of secs. 32 and 33, re-established as angle point, bears N.36°25'E., 4.21 chs. dist.)

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-31

Found - Iron Pipe with brass cap mkd. T27S R7W S32|S33 AP5
1924
16" Fir stump N.66°E., 18.5 ft. shows good scar.
36" Laurel N.67°W., 26.4 ft. alive & in good condition. Didn't open.
New BTs - 24" Laurel N.39°E., 16.6 ft. mkd: T27S R7W S33 CSBT.
Corner lies about 10 ft. west of fence corner (new fence). Fence runs E and N.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20000)