

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5254)

-----  
Set 1/4 sec. post, from which  
    A W.Oak 24" dia., bears N.1°W., 42 lks. dist.  
    A B.Oak 15" dia., bears N.62°E., 13 lks. dist.

-----  
GLO survey by Fred Mensch under Contract #109 dated 1924 (DCSO records, Vol. 14 Page 5857)

-----  
Intersect the 1/4 sec. cor., located by record bearing and distance from stump hole of original NE bearing tree, dead, down, and rotten. marks are legible on the overgrowth. No trace found of the original NW bearing tree. At the exact cor. point, Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for cor., with brass cap marked:

1/4  
    S32|S33  
    |SP 4  
    1924

from which (new bearing trees)  
    A W.Oak 6" dia., bears S.29°E., 32 lks. dist. marked 1/4 S 33 BT.  
    A Fir 30" dia., bears N.20°W., 10 lks. dist., marked 1/4 S32 BT.  
Bearing of old NE stump hole is N.62°E., 13 lks. dist.

-----  
BLM dependent resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO records Vol. 50 Page(s) 19141-42)

-----  
From the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 2" above ground, with brass cap mkd.

1/4  
    S 32     S 33  
    AP 4  
    1924

from which the remains of the bearing trees mkd. by Mensch  
    A sawed oak stump, 6 ins. diam., bears S. 29° E., 32 lks. dist., no marks visible.  
    A sawed fir stump, 28 ins. diam., bears N. 20° W., 10 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees  
A cedar, 16 ins. diam., bears N. 67° E., 43½ lks. dist.,  
mkd. ¼ S33 BT.  
An oak, 16 ins. diam., bears S. 53° W., 54 lks. dist.,  
mkd. ¼ S32 BT.  
The corner is located 2 lks. N. of a corner of wire fences,  
extending N., S., and E.