

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5254)

Set post, cor. sec. 28, 29, 32 and 33, from which
A B.Oak 15" dia., bears N.48°E., 93 lks. dist.
A B.Oak 20" dia., bears S.60°E., 73 lks. dist.
A B.Oak 10" dia., bears N.35°W., 69 lks. dist.
A B.Oak 15" dia., bears S.50°W., 59 lks. dist.

GLO survey by Fred Mensch under Contract #109 dated 1924 (DCSO records, Vol. 14 Pages 5856-57)

Intersect the cor. of secs. 28, 29, 32 and 33, located by record bearing and distance from the original NW bearing tree, now dead, old blazes plain, but marks rotted away. At the exact cor. point, Set an Iron post, 3 ft. long, 2" dia., 28" in the ground, for corner, with brass cap marked:

T27S R7W
S29|S28
S32|S33
|AP 3
1924

from which (new bearing trees)
A Fir 10" dia., bears N.12°E., 15 lks. dist. marked
T27S R7W S28 BT.
A Fir 10" dia., bears S.38°E., 16 lks. dist. marked
T27S R7W S33 BT.
A Fir 14" dia., bears S.56°W., 16 lks. dist. marked
T27S R7W S32 BT.
A Fir 14" dia., bears N.56°W., 41 lks. dist. marked
T27S R7W S29 BT.

Original bearing tree, a dead Oak 12" dia., bears N.35°W., 69 lks. dist.

Stump hole of orig. BT, rotted or burned out, bears N.48°E., 93 lks. dist.

Decayed stump of orig. BT, an Oak, bears S.50°W., 59 lks. No trace is found of original SE bearing tree.

Doug. County Surveyors Office - James Byron, Deputy - Ray Irving; John Fee - Feb. 3, 1955 - C.S. File 46/90

Found - Brass cap at cor. and stump of 14" R.Fir N.12°E., 15 lks. dist.

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Also find stump of 14" R.Fir S.56°W., 16 lks.
scribing visible. All other BTs gone.
Blazed and scribed:
14" B.Oak N.1°E., 7.6 ft. "T27S R7W S28 CS BT."
14" R.Fir N.61½°W., 70.5 ft. "T27S R7W S29 CS BT".
10" R.Fir S.38½°E., 25.7 ft. "T27S R7W S33 CS BT".
8" R.Fir S.28°W., 66.0 ft. "T27S R7W S32 CS BT".

Fd. & used BLM resurvey by Philip G. Griffin, Cadastral
Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO
Records Vol. 50 Page(s) 19142-43)