

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec Cor for 28, 29, 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5255)

Set Post, cor. secs. 20, 21, 28 and 29, from which
An Ash 12" dia., bears N.89½°E., 1323 lks. dist.
An Ash 9" dia., bears S.66°W., 366 lks. dist.
A W.Oak 20" dia., bears S.60°E., 1148 lks. dist.
An Alder 20" dia., bears N.80°W., 325 lks. dist.

Don E. Garrett, for: Hayward Reed - Jan. 1, 1968 - M 33-27

Found - Ash clump in position of O.B.T., S.66°W., 366 lks.
Set - Brass cap stamped "W.C. Sec. 20, 21, 28 and 29, T27S
R7W 14.57 ft. East to Cor. LS 544".

Scribed BT:
8" Ash bears N.80°W., 177.8 ft. scribed WC S20 T27S
R7W BT.

Fd. by Mark Smalley - For: Roseburg Resources Co. - May 1999 -
M 132-13

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 3/6/2024 - C.S. File 67/57-41

Found - 2½" brass cap on 1" I.D. iron pipe up 2".
14" Ash fallen SW still alive new upright trunk
forming N.80°W., 177.8 ft., fully healed
single blaze.

New - From Garrett survey M33-27 Two Touchstone Lane R/W
pins:

5/8" I.Rod proj. 1" bears S.28¾°E., 90.4 ft.

5/8" I.Rod proj. 1" bears N.28¾°E., 269.4 ft.

Note - Mon. on flat pasture ground 35' east of center line
Touchstone Lane.

Compass decl. 14½°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

N 133643.852 E 107510.264