

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5256)

-----  
Set ¼ sec. post, from which  
    A W.Oak 30" dia., bears N.54°E., 485 lks. dist.  
    A W.Oak 20" dia., bears N.88°W., 411 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy  
Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-76

-----  
Found - Orig. 30" now 54" W.Oak N.54°E., 320.0 ft. We open  
          & find good scribing "S".  
          Orig. 20" now 48" W.Oak N.88°E., 271.3 ft. Shows  
          faint scar. I do not open.  
BTs check record bearing but distances are each 5.6 ft.  
greater than record.  
This corner in field. I SET WIT. COR. 174 ft. North and in  
E-W fence line.  
Set Brass cap mkd: "Wit. Cor. 174' South to ¼ S20|S21 T27S  
          R7W".  
New BTs - 11" W.oak bears N.9°W., 39.4 ft. scribed ¼ S20 CSBT  
          10" W.Oak bears N.60°E., 41.5 ft. scribed ¼ S21 CSBT