TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Pages 5257-58)

---

Set ¼ sec. post, from which
A B.Oak 36" dia., bears S.58°E., 68 lks. dist.
A W.Oak 12" dia., bears S.20°W., 37 lks. dist.

---

Doug. County Surveyors Office - James Byron, Deputy
Milo Godfrey; Clete Putnam - Jan. 1961 - C.S. File 49/79-3

---

Found - Orig. 12" now 20" W.Oak snag. We open & find good scribing, reverse scribing "B"
Shell of large Oak bears S.32°E., 17.4 ft. (Rec. S.58°E., 44.9 ft.) NW portion of Oak gone. This shell checks record dist. & brg. from 3" x 12" x 18" stone with + on top which has been used for ¼ cor. for 50 years ±, states Paul Dimmer.
The W. Oak faces to our corner and I believe the record dist. & brg. to SE (Oak shell) is in error.
Set Brass cap at cor. mkd: County Surveyor's Office, 1961
¼ S17|S16 T27SR7W
Stone with cross bears N.72°W., 28.8 ft. from Brass cap.
New BTs - 11" W.Oak bears N.7°W., 11.3 ft. scribed ¼ S17 CSBT
8" W.Oak bears S.74°E., 16.8 ft. scribed ¼ S16 CSBT.

---

Carl Sweeden - For: Roseburg Resources Co. - Dec. 2006 - M151-78

---

Found - 2½" DCSO brass cap "1961" up 0.9' leaning slightly 3"x12"x18" stone w/"X" upside down @ N.72°W., 28.8'
15" W.Oak BT N.7°W. 11.3' double blaze healed & scar
12" W.Oak BT S.74°E., 16.8' double blazed.
New BTs - 7" W.Oak BT S.68°W., 13.1', scribed "E¼ S17 BT", tagged.

---

Fd. OK by C. Sweeden 8/2007 - M155-40
Fd. Ok by M. Brittain, 4/2011 - M157-40A&B