

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 5259)

Set post, cor. secs. 4, 5, 8 and 9, from which
A Laurel 15" dia., bears N.65°W., 9 lks. dist.
A Cedar 15" dia., bears S.55°W., 14 lks. dist.
A Fir 24" dia., bears N.55°E., 38 lks. dist.
A Fir 15" dia., bears S.65°E., 92 lks. dist.

Briggs/Frear, for: Sol Mendell, July, 1884 - Vol 1 Pg 39

Set Rock 30 x 18 x 10 by BT.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-69

Found - Orig. 15" now 30" dead Cedar, partly burned, S.55°W., 9.2 ft. shows scars.
Orig. 24" now 32" partly rotted Fir stump, S.65°E., 60.7 ft. We open & find good scribing "BT"
Stump of orig. NE BT, & orig. NW BT gone.
16" x 8" x 16" corner stone with + on top at 4-way fence intersection.
Corner stone is good. We do not set Brass cap.
New BT - 6" Laurel bears N.86°W., 37.6 ft. scribed S5 CS BT.
No other trees near.

Doug. County Surveyors Office - James Byron, Co. Surveyor John Powell and crew - Jan. 21, 1970 - C.S. 54/99 and M 39-16

Found - 30" Cedar snag S.55°W., 9.2 ft., face burnt.
6" Laurel now 11" N.86°W., 37.6 ft. scribe marks visible.
16" x 8" x 16" corner stone in 4-way fence corner.
Set Brass cap at cor. mkd: County Surveyor's Office
T27S R7W
S 5 | S 4
1970 S 8 | S 9
New BTs - 6" Laurel N.83°E., 8.6 ft. mkd: T27S R7W S4 CSBT
6" Laurel S.34°W., 9.8 ft. mkd: T27S R7W S8 CSBT

Found brass cap and accessories per record. Donald Bentz, for: Fred Engle - Oct. 1992 - Partition 1993-0018

Found OK by K. DeGroot, Aug. 2001 - M138-60
Found OK by T. Hostetter, June 2002 - M140-54

continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 4/6/2006 - C.S. File 67/14-9

Found - 2½" dia. brass cap on 1¼" O.D. IP (properly mkd)
projects from ground 15".
Stone 15"x26"x10" is fd. lying on East side of BC/IP
(Briggs 1884)
11" Laurel now 20" dia., x 1 ft. tall stump bears
N.84°W., 37.6 ft (rec. N.86°W. 37.6 ft) 1960 BT
Stump hole fd. near rec. bearing & dist. form orig.
SE BT (Rec. 15" fir bears S.65°E., 60.7 ft) OBT
No trace of other previous BTs found.
New - 17" dia., W.Fir double blazed & scribed "T27S R7W S9
CS BT" bears S.84°E., 36.0 ft.
20" dia., D.Fir double blazed & scribed "T27S R7W S5
CS BT" bears N.87¼°W., 55.0 ft.
Double trunked Madrone, southerly trunk is 14" dia.,
& is scribed "T27S R7W S4 CS BT" bears
N.57¾°E., 27.1 ft.
15" dia., madrone with previously sawn main trunk
double blazed & scribed "T27S R7W S8 CS BT"
bears S.13½°W., 52.3 ft.
Note - Corner lies on gentle north east slope in 3 way
fence corner with fences extending North, South
& West. Recent clearcut to the North East.
Compass decl. 16¼°E.

Fd. BC & 4 BTs by Ron Rice 3/2009 M158-80

Ron Quimby - For: Weyerhaeuser - June 2017 - M173-35

Found - Brass cap per 1970 renewal
20"x12" tall madrone stump bears N.84°W., 37.6'
15" Double trunked madrone bears N.58°E., 27.1'
partially visible scribe
22" Fir bears S.84°E., 36.0' - healed face
15" Madrone bears S.13°W., 52.3' partially visible scribe
22" Fir bears N.87°W., 55.0' - healed face
B0 - 15"x26"x10" stone on east side of brass cap