

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/14 Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5254)

Set ¼ sec. post, from which
A B.Oak 15" dia., bears N.31°E., 180 lks. dist.
A B.Oak 12" dia., bears S.87°E., 195 lks. dist.

GLO survey by Fred Mensch under Contract #109 dated 1924 (DCSO records, Vol. 14 Pages 5855-56)

Intersect the ¼ sec. cor., located by measurement from the original bearing trees, old marks plain. The SW. tree is dead. At the exact cor. point, Set an iron post, 3 ft. long 1" dia., 26" in the ground, for ¼ cor., with brass cap mkd:

¼ $\frac{S28}{S33}$
AP 2
1924

from which
A B.Oak 24" dia., bears N.31°E., 180 lks. dist., marked ¼ S 28 BT. (Original BT)
A W.Oak 10" dia., bears S.17°E., 14 lks. dist., marked ¼ S33 BT. (New BT)
Original bearing tree, a dead Oak, 15" dia., bears S.87°E., 195 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - Jan. 1961 - C.S. File 49/79-25

Found - Gov't Brass cap at corner.
24" B.Oak N.31°E., 180 lks., good scribing visible in open scar. Tree nearly dead)
10" W.Oak S.17°E., 9.2 ft. scar open, face nearly rotted away.
New BTs- 15" Pine S.79°W., 5.3 ft. mkd. ¼ S33 CS BT.
10" D.Fir N.13°E., 89.6 ft. mkd. ¼ S28 CS BT.
New fence line E & W through corner.

Fd. & used BLM resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO Records Vol. 50 Page(s) 19144)

Mark Smalley - For: Roseburg Resources Co. - May 1999 - M 132-13

Found - 1924 GLO brass cap on IP.
9" (10") W.Oak S.17°E., 9.2 ft., healed.
continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/14 Cor Secs 28 & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

24" B.Oak N.31°E., 118.8 ft. snag scribe vis., orig.
22" Fir N.13°E., 89.6 ft., healed.
Remnant of a Pine face scribed "¼ S33 CS BT" no tree
New BT - 6" Oak S.64°E., 22.0 ft., "¼ S BT"
20" Fir N.43°E., 92.1 ft., "¼ S BT"

Fd. Ok by Neil Hibbs, 8/2006 - M146-72