

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

1960: A 2½" dia., brass cap (properly mkd) on 1" I.D. iron pipe is firmly set and protrudes approx. 14" above ground on W edge of stone. Pointed top of fd. stone and center of slightly leaning BC monument are essentially concentric; accessories are measured from center of BC. No evidence of Orig. BTs
1934: A 24" fir, now a 4 ft. tall approx. 26" dia., partially rotted fir stump with the scribing "CS BT" visible on a previously opened single blaze; bears S.63°W., 18.0 ft. (rec. S.60°W., 18.0 ft)
1934: An 18" Fir, now a 1 ft. tall approx. 24" dia., very rotted Fir stump which is broken opened to find the scribing "S BT" in blaze remnant; bears N.17°W., 45.0 ft. (as per rec)
1974: North craft survey (M52-26) A ⅝"x30" iron rod is lying loose on surface of ground westerly 15+ ft. from BC monument (Rec. S.89°38'W. 15.1 ft)
Monuments are in good condition; we do not disturb.
New - An 11" DBH B.Oak scribed "¼ S9 CS" "BT" on a double blaze; bears N.49°E., 28.9 ft.
A 16" DBH G.Fir scribed "¼ S9 CS" "BT" on a double blaze; bears S.39°E., 35.7 ft.
A 5" DBH strongly pistol butt madrone scribed "X" "CS" "BT" on a high low double blaze; the center of the root crown of which bears S.15°W., 10.5 ft
A 10" DBH G.Fir scribed "¼ S4 CS" "BT" on a double blaze; bears N.9½°W., 71.4 ft.
Note - Corner is on gentle NE slope which is clear cut to the SW and is covered in mixed older forest to NW, NE & SE.
Compass decl. 15¾°E.