

PRIMARY CORNER DESCRIPTION Sec Cor. for 33 & 34 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, Deputy under Contract #44 dated May 30, 1854 (DCSO Records, Volume 12 Page 5220)

Set a post, cor. of secs. 33 and 34, from which
 A Laurel 12" dia., bears N.65°W., 25 lks. dist.
 A Laurel 15" dia., bears N.83°E., 87 lks. dist.
for closing corner.

GLO survey by Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5224 and Pg. 5232)

Set post, cor. secs. 33 and 34, from which
 A B.Oak 12" dia., bears N.46°E., 63 lks. dist.
 A B.Oak 12" dia., bears N.75°W., 15 lks. dist.
Corner set by Ford, bears North 115 lks. and East 73 lks.

GLO survey by Fred Mensch, Contract #109 dated 1924 (DCSO records, Volume 14 Page 5836)

Fall 9 lks. S. of the cor. of secs. 33 and 34, established by Hathorn. From this cor. the cor. established by Ford for cor. of secs. 33 and 34, in sight, bears N.32°E., 1.37 chs.

(Same Deputy, Same contract) (DCSO records, Vol 14 Pgs 5842-43)

Intersect the cor. of secs. 33 and 34, located by record bearing and distance from the original NE. bearing tree, marks legible. No trace is found of the original NW. bearing tree. At the exact cor. point, Set an iron post, 3 ft. long 2" dia., 27" in the ground, for cor. of secs. 33 and 34, with brass cap marked:

 T27S R7W
 AP 12 S33|S34
 1924

from which (new bearing trees)
 A Fir 14" dia., bears N.63°E., 33 lks. dist., marked
 T27S R7W S34 BT.
 A Fir 12" dia., bears N.6°W., 13 lks. dist. marked
 T27S R7W S33 BT.

 The original bearing tree in sec. 34, a black oak, 20" dia., bears N.46°E., 63 lks. dist.
 The cor. established by Ford for cor. of secs. 33 and 34, restored as angle point, bears N.32°E., 1.37 chs. dist.

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor for 33 & 34 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - James W. Byron, Deputy; Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-23

Found - Stump, now 18", N.63°E., 21.8 ft. shows old scars & burned areas. No scribing found.
Also find AP which bears N.32°E., 90.4 ft., checks dist. & bearing. We do not find NW BT.
Find brass cap (1924 survey) laying on stump near corner.
Reset brass cap at corner & 1.5 ft. West of new wire fence.
New BTs - 8" R.Fir bears N.60¾°W., 94.0 ft. scribed T27S R7W S33 CS BT.
9" R.Fir bears N.60°E., 102.2 ft. scribed T27S R7W S34 CS BT.