

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5248)

Set post, cor. secs. 27, 28, 33 and 34, from which
A W.Oak 18" dia., bears S.49°W., 128 lks. dist.
A B.Oak 12" dia., bears S.1°E., 84 lks. dist.
A B.Oak 18" dia., bears N.17°W., 100 lks. dist.
A B.Oak 12" dia., bears N.1°E., 120 lks. dist.

GLO survey by Fred Mensch, under Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5854-55)

Corner located by measurements from the original bearing trees, all found. The SE tree rotted down and the SW tree badly decayed. At the exact cor. point, Set an iron post 3 ft. long 2" dia., 28" in the ground, for corner, with brass cap marked:

T27S	R7W
S28	S27
S35	S34
AP 1	
	1924

from which

(old bearing tree) A B.Oak now 20" dia., bears N.1°E., 120 lks. dist., mkd. T27S R7W S27 BT.
(new bearing tree) A Fir 8" diam., bears S.27°E., 21 lks. dist., mkd. T27S R7W S34 BT.
(new bearing tree) A Fir 12" dia., bears S.29°W., 12 lks. dist., mkd. T27S R7W S33 BT.
(old bearing tree) A B.Oak now 24" dia., bears N.17°W., 100 lks. dist. re-marked T27S R7W S28 BT.
Old bearing tree, an Oak 24" dia., bears S.49°W., 128 lks.
Orig. position of old bearing tree, an Oak, rotted out, bears S.1°E., 84 lks.

Doug. County Surveyors Office - James Byron, Deputy
Milo Godfrey; Clete Putnam - Nov. 1960 - C.S. File 49/79-58

Found - Brass cap set in 1924 survey.
Stump of 8" Fir S.27°E., 13.9 ft. scribe marks visible in open scar.
Stump of 12" Fir S.29°W., 7.9 ft. showing scar.
Rotted remnants of old Oak BTs to NW & NE found too far gone for any possibility of scribing to be found.

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Blazed and scribed new BTs:
15" Fir S.65½°W., 13.7 ft. mkd. "T27S R7W S33 CS BT"
6" Fir N.79°W., 25.6 ft. mkd. "S28 CS BT".
8" Fir S.16½°E., 50.4 ft. mkd. "T27S R7W S34 CS BT".
8" Fir N.57°E., 63.5 ft. mkd. "T27S R7W S27 CS BT".

Fd. & used BLM resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO Records Vol. 50 Page(s) 19138-39)

Mark Smalley - For: Roseburg Resources Co. - May 1999 - M 132-13

Found - 1924 GLO brass cap on IP.
22" Fir S.65½°W., 13.7 ft., healed.
11" Fir N.79°W., 25.6 ft., healed.
8" Fir S.16½°E., 50.4 ft., healed.
13" Fir N.57°E., 63.5 ft., healed.

New BT - 8" Fir N.34°E., 40.6 ft., "S 27 BT"