

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Pages 5248-49)

-
- Set ¼ sec. post, from which
 - A B.Oak 12" dia., bears S.32°E., 63 lks. dist.
 - A B.Oak 12" dia., bears N.62°W., 112 lks. dist.

Doug. County Surveyors Office - Ben B. Irving, Co. Surveyor Jim Byron; Ray Irving; John Fee - March/April 1954 - C.S. File 45/262

-
- Found - Orig. BT, 20" B.Oak S.32°E., 63 lks. in good condition.
 - Also found leaning snag with possible old blaze. No scribes visible. Checks for bearing and distance, a yellow tag near this snag states that Jack Chapman found scribes on snag in 1945.
 - Set 1" Iron pipe with brass cap mkd: County Surveyors Office 27|28 T27S R7W 1954.
 - Blazed and scribed the following trees:
 - 10" Red Fir S.54°E., 62.0 ft. mkd. ¼ Sec. 28 CS BT.
 - 10" Red Fir S.17°W., 20.6 ft. mkd. ¼ S28 CS BT.

Doug. County Surveyors Office - Larry E. Monrean, Deputy K. Reed; K. Mosley - April 29, 1980 - C.S. File 61/6-37

-
- Found - A 1" x 36" I.P. with 1954 DCSO cap, properly mkd., protruding 0.8 ft. above ground.
 - An Orig. 12" B.Oak now a 22", 2 ft. high stump bears S.34°E., 42.2 ft. (Rec. S.32°E., 41.6 ft.) The dist. 41.6 ft. is face measurement. We open stump to find old axe marks and orig. scribing "BT".
 - An orig. 12" B.Oak, now a rotted stump of indeterminate size bears N.60°W., 73.9 ft. (Rec. N.62°W.)
 - A 10" Fir now a 17", 1 ft. high stump, bears S.18½°W., 20.6 ft. (Rec. S.17°W)
 - A 10" Fir, now tipped out with visible scribe "¼ S27" (rec. ¼ S28) roothole bears S.56½°E., 62.0 ft. (Rec. S.54°E.)
 - Left cap in position.
 - New BTs -
 - 10" Fir scribed "1/4 S27 CS BT" in a double blaze bears S.7°E., 56.3 ft.
 - 7" Fir scribed "1/4 S27 CS BT" in a double blaze bears N.43½°E., 4.4 ft.
- continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>8" Fir scribed "1/4 S28 CS BT" in a double blaze bears N.41°W., 9.7 ft. 9" Fir scribed "1/4 S28 CS BT" in a double blaze bears S.40½°W., 25.3 ft.</p>
<p>Found OK, February 1991, M 111-79</p>
<p>Fd. & used BLM resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO Records Vol. 50 Page(s) 19147-48)</p>
<p>Mark Smalley - For: Roseburg Resources Co. - May 1999 - M 132-13</p> <p style="text-align: center;">-----</p> <p>Found- 1954 County Brass cap on IP. 7" Fir N.43½°E., 4.4 ft., down, rotted. 18" Fir S.7°E., 56.3 ft., healed. 18" Oak stump S.34°E., 42.2 ft. rotten, orig. 15" Fir S.40½°W., 25.3 ft., healed 12" Fir N.41°W., 9.7 ft., healed. 17" Fir stump S.18½°W., 20.6 ft., rotten. New BT - 16" Fir N.3°E., 12.6 ft. "¼ S BT"</p>