

PRIMARY CORNER DESCRIPTION (WC) Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5250)

Set post, cor. secs. 15, 16, 21 and 22, from which
A W.Oak 30" dia., bears N.25°W., 683 lks. dist.
A W.Oak 30" dia., bears N.77°E., 109 lks. dist.
A W.Oak 20" dia., bears S.27°W., 332 lks. dist.
A W.Oak 20" dia., bears S.39°E., 33 lks. dist.

Ben B. Irving, County Surveyor; Jim Byron; Ray Irving; John Fee - March/April 1954 - C.S. File 45/262

Corner renewed from stump of orig. BT:
20" W.Oak S.39°E., 33 lks. dist.
Also found old rotted stumps that check for size, bearings & distances for NE and SW BTs:
30" W.Oak N.77°E., 109 lks.
20" W.Oak S.27°W., 332 lks.
Set a 1"x36" Iron pipe with brass cap mkd: 15, 16, 21, & 22, T27S R7W 1954, County Surveyors Office. Set cap 4" under road surface.
Blazed and scribed the following:
14" B.Oak S.39°15'W., 50.0 ft. S21 CS BT.
10" B.Oak N.17½°W., 85.8 ft. S16 CS BT.
16" B.Oak N.30°E., 80.5 ft. S15 CS BT.

Found OK, Vernon Tracy, Sept. 18, 1968 C.S. File 54/23-28A

Doug. County Surveyors Office - John Powell; Frank Jones; W Penley - Dec. 9, 1969 - C.S. File 54/23-32

Found - 1954 DCSO brass cap 6" under surface of road.
14" now 17" B.Oak S.39°W., 50.0 ft. some scribe marks visible.
10" now 12" B.Oak N.17½°W., 85.8 ft., some scribe marks visible.
16" B.Oak stump N.30°E., 80.5 ft. opened for scribe. (This tree will be in road.)
Reset Brass cap for WIT COR. mkd: County Surveyor's T27S R7W
Office W.C. 32' S16|S15
1954 to east S21|S22
New BTs - 15" W.Oak N.45°E., 115.4 ft. mkd: W.C. T27S R7W
S15 CS BT.
8" W.Oak N.4°W., 14.6 ft. mkd: W.C. T27S R7W S16
CS BT.
8" D.Fir S.14½°W., 20.2 ft. mkd: W.C. T27S R7W S21
CS BT.
This Witness Corner lies in N-S fence line.

Cont.

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION (WC) Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ronald Quimby, L.S. #1654, for: Richard Kilduff - May 1984
C.S. File 58/284 and M 96-55

Found - 1½" I.P. with 2½" Brass cap, properly marked.
14" W.Oak bears N.45°E., 115.4 ft., visible scribe
"7 W".
8" W.Oak bears N.5°45'W., 14.6 ft. (N.4°W) with
healed blaze.
14" D.Fir bears S.16°30'W., 20.2 ft. (S.14°30'W)
healed blaze.
New BT - 11" W.Oak bears N.0°30'E., 79.7 ft. with healed
blaze. This BT was not previously of record.

Fd. OK, M. Ramp, April 1989, M 107-79

Marc Brittain - 4/2011 - M157-40 A&B

Condition report
Found 2½" brass cap mon. (+1.0' AGL) in wire fencing.
14" W.Oak bears N.45°E., 115.4' with tag.
8" W.Oak bears N.5°45'W., 14.6' with tag.
11" W.Oak bears N.0°30'E., 79.7' with tag.
14" D.Fir of record not recovered.

Fd. by M. Brittain, 11/2012 - M165-25