

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5251)

Set post, cor. secs. 9, 10, 15 and 16, from which
A B.Oak 12" dia., bears S.16°W., 71 lks. dist.
A B.Oak 15" dia., bears S.71°E., 58 lks. dist.
A W.Oak 12" dia., bears N.32°W., 171 lks. dist.
A W.Oak 15" dia., bears N.20°E., 84 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - For: C.L. Brown - Wit. Milo Godfrey; Clete Putnam - August 19, 1960 - C.S. File 52/41

Found - Orig. 12" now 18" Oak snag N.32°W., 112.9 ft. I open & find good scribing "BT".
Orig. 15" now 24" W.Oak N.20°E., 55.4 ft. shows scar. I do not open.
No trace of SE or SW BTs found.
Set Brass cap at cor mkd County Surveyor's $\frac{S\ 9|S\ 10}{S16|S15}$ T27SR7W
Office, 1960
Corner is located thus. (See sketch in C.S. File)
New BTs - Rescribe W.Oak now 24" N.20°E., 55.4 ft. S10 T27S R7W CS BT.
21" R.Fir bears N.54°W., 82.6 ft. scribed S9 T27S R7W CS BT.
5" W.Oak bears S.24°W., 62.8 ft. scribed S16 CS BT.

Found OK, Vernon Tracy, Sept. 18, 1968 C.S. file 54/23-28A

Doug. County Surveyors Office - John Powell; Frank Jones; W. Penley - Dec. 9, 1969 - C.S. File 54/23-35

Found - Orig. 15" now 27" W.Oak N.20°E., 55.4 ft. shows good scar.
1960 DCSO brass cap. This cor. to fall in road due to new construction. Remove brass cap and reset for WITNESS CORNER.
21" now 23" D.Fir N.54°W., 82.6 ft shows good scar.
15" now 18" D. Fir S.61°E., 125.5 ft. shows good scar.
Reset Brass cap for Wit. Cor. mkd: County Surveyor's T27S R7W
Office W.C. 25 ft. $\frac{S9|S10}{S16|S15}$
1969 South to
Reblaze and rescribed:
27" W.Oak N.41½°E., 33.3 ft. mkd. WC T27S R7W S10 CS BT.
23" D.Fir N.71°W., 69.7 ft. mkd. W.C. T27S R7W S9 CS BT.
continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

18" D.Fir S.53°E., 140.8 ft. mkd. W.C. T27S R7W S15 CS BT. 5/8" R/W pine, S.57°E., 18.2 ft. Station 217+00.
Found OK, Ron Quimby, May 1984, M 96-55
Donald Bentz, For: Fred Engle - Oct. 1992 - Partition plat, 1993-0018 ----- Set Witness Corner. Set 5/8" Iron rod with cap marked "i.e. Engineering". True corner is 25 ft. South. Accessories per record.
Fd. Ok by M. Brittain, Nov. 2010 - M157-34
Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/30/2023 - C.S. File 67/55-66 ----- Found - 1969 DCS0 brass cap (properly mkd) up 1" 5/8" I.Rod with ie engineering plastic ap 0.35 ft south. 28" W.Oak N.38°E., 33.3 ft. (rec. N.41½°E.) full healed double blaze, re-blaze, add 3½" mag nail right side center. New - 5/8"x30" I.Rod with DCS0 plastic cap up 3" bears S.10°E., 20.0 ft. 5/8"x30" I.Rod with DCS0 Plastic cap up 3" bears S.67°W., 23.4 ft. Note - Compass decl. 14½°E. Oregon Coordinate Reference System Cottage Grove - Canyonville Zone N 144241.344 E 112805.489