

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5252)</p> <p>-----</p> <p>Set ¼ sec. post, from which A B.Oak 12" dia., bears S.75°E., 68 lks. dist. A B.Oak 10" dia., bears N.70°W., 93 lks. dist.</p>
<p>Doug. County Surveyors Office - James Byron, Deputy Milo Godfrey; Clete Putnam - 8/19/1960 - C.S. File 52/41 & M 19-42</p> <p>-----</p> <p>Found - Both orig. BTs. Each now down & mostly rotted, but each has parts of old faces showing good reverse scribe marks. Check record size, species, bearing and distance. Corner 2 ft. West of N-S fence. Set Brass cap at cor. mkd: County Surveyor's Office, 1960 ¼ S 9 S 10 T27S R7W New BTs- 19" R.Fir bears S.33°W., 23.5 ft. scribed ¼ S9 CS BT 10" R.Fir bears S.39°E. 38.4 ft. scribed ¼ S10 CS BT</p>
<p>Found OK, 1986, M 100-18</p> <p>Found Brass cap accessories per record - Donald Bentz, Oct. 1992, Partition plat 1993-0018</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/6/1999 - C.S. File 66/12-18</p> <p>-----</p> <p>Found - 2½" dia. brass cap on a 1½" O.D. iron pipe protrudes 15" above ground, properly marked. 1960 8"x8"x16" stone found firmly set and plumb, protrudes 6" above ground. No marks found, bears N.52°W., 1.8 ft. Possibly set by Briggs in 1884? See V. 1 P. 39 & 40. This corner shown as a fd. rock in 1913 by Frank Cain, Doerner's Add. to Eden Orchards Subd. Vol. 4Pg. 3.</p> <p><u>Bearing & dist. taken from BC/IP</u> 10" now 16" dia., 4 ft. high D.Fir stump with fully healed double blaze bears S.39°E., 38.4 ft. (agrees w/rec.) 1960 19" now 24" dia., 1 ft. high D.Fir stump w/fully healed blaze, bears S.33°W., 23.5 ft. (Agrees w/rec.) 1960 Both OBTs now gone.</p> <p>Set - <u>Bearing & dist. taken from BC/IP</u> 5" dia., Madrone bark scribed "¼ S9 CS BT" bears S.1½°W., 24.4 ft. continued next page</p>

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" dia., B.Oak double blazed & scribed "¼ S10 CS
BT" bears S.39°E., 31.0 ft.
4" dia., D.Fir double blazed & scribed "X CS BT"
bears N.67°E., 30.3 ft.
13" dia., D.Fir double blazed & scribed "¼ S9 CS BT"
bears S.44°W., 77.6 ft.
Corner lies 3 ft. west of an N-S fence line.