

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5252)</p> <p>-----</p> <p>Set post, cor. secs. 3, 4, 9 and 10, from which</p> <ul style="list-style-type: none">A B.Oak 36" dia., bears S.83°E., 86 lks. dist.A B.Oak 30" dia., bears N.60°W., 99 lks. dist.A B.Oak 12" dia., bears S.65°W., 236 lks. dist.A B.Oak 8" dia., bears N.2°E., 102 lks. dist.
<p>Briggs and/or Frear, July, 1884 - Volume 1 Pages 39-40</p> <p>-----</p> <p>Set rock 24 x 12 x 8 by BT.</p>
<p>Doug. County Surveyors Office - James Byron, Deputy; Milo Godfrey; Clete Putnam - August 1960 - C.S. File 49/79-45</p> <p>-----</p> <p>Found - Orig. 36" now 40" down Oak S.83°E., 56.8 ft., shows good reverse scribing "S10".</p> <p>Orig. 12" now 16" rotted stump, good reverse scribing "BT", S.65°W., 155.8 ft.</p> <p>No trace of NE BT. found.</p> <p>Found Oak stump hole that checks for orig. NW BT.</p> <p>Find 12" x 8" stone at cor. with + chisled on top.</p> <p>Corner stone is good monument. Do not set brass cap.</p> <p>New BTs-</p> <ul style="list-style-type: none">9" Laurel bears N.50°W., 17.5 ft. scribed S4 T27S R7W CS BT.10" cedar bears N.63°E., 19.2 ft. scribed S3 T27S R7W CS BT.6" R.Fir bears S.27½°W., 42.5 ft. scribed S9 T27S R7W CS BT.21" Cedar bears S.55°E., 25.2 ft. scribed S10 T27S R7W CS BT.
<p>Doug. County Surveyors Office - Randall Smith, Stephen Flaese - June 6, 1993 - C.S. File 64/43-27</p> <p>-----</p> <p>Found - Stone, 12"x8"x5" above ground with 2" 'X' chiseled on top. (1884 Briggs)</p> <ul style="list-style-type: none">3/4" shaft protrudes 10" above ground is found along south edge of stone. (source unknown)4"x4" cedar post protruding 5" above ground is along south edge of stone. (source unknown) <p>Accessories Found -</p> <ul style="list-style-type: none">9" now 14" dia. Madrone with a fully healed double blaze, bears N.50°W., 17.5 ft. (1960 Byron)10" now 18" dia. Cedar with a fully healed double blaze, bears N.63°E., 19.2 ft. (1960 Byron) <p>continued next page</p>

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" now 15" dia. 3 ft. high D.Fir stump with a fully healed blaze, bears S.27½°W., 42.5 ft. (1960 Byron) Stump will be removed by land owner in near future.

21" now 34" dia. Cedar with a fully healed double blaze, bears S.55°E., 25.2 ft. (1960 Byron)

Orig. 36" now 24" dia. down & rotted Oak. No blazes or scribing visible bears S.83°E., 56.8 ft.

Orig. SW BT now gone.

New Accessories -
Power Pole "2F313" bears S.77°W., 90.9 ft.

Note - Corner lies at the intersection of a four way fence corner.

Fd. ok by Raymond Brown, May 1998 - M129-4
Fd. ok by Carl Sweeden, 4/2002 - 2002-0018A&B