

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5253)

-----  
Set ¼ sec. post, from which  
    A W.Oak 12" dia., bears N.42°W., 57 lks. dist.  
    A W.Oak 15" dia., bears S.58°E., 109 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy  
Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-74

-----  
Found - Both orig. BTs.  
    15" now 20" Oak snag S.58°E., 71.9 ft. We open &  
        find good scribing "B".  
    12" now 18" Oak snag (Rec. N.42°W., 37.6 ft., we  
        find to be N.26°W., 37.6 ft. This BT was also  
        opened & good scribing found "¼S".  
Set Brass cap at corner. (See C.S. File for sketch)  
New BTs - 5" W.Oak S.4°E., 47.5 ft. scribed ¼ S3 CS BT.  
    10" W.Oak bears S.84½°E., 90.3 ft. scribed ¼ S3 CSBT

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 1/21/1999 - C.S. File 66/8-4

-----  
Found: 2½" dia. brass cap on a 1½" iron pipe protrudes 14"  
        above ground. 1960  
No OBTs found.  
    5" now 11" dia. W.Oak with a fully healed double  
        blaze, bears S.4°E., 47.5 ft. 1960  
    10" now 15" dia. W.Oak with a rotted blaze, scribing  
        visible "B", bears S.84½°E., 90.3 ft. 1960  
New: 11" dia. Madrone double blazed and scribed "1/4 S4  
        CS BT" bears N.34°W., 139.5 ft.  
    4" dia. W.Oak double blazed and scribed "XBT",  
        bears S.49°E., 49.5 ft.

Found OK by G. Lang, Oct. 2004 - M145-80 A & B  
Fd. Ok by C Sweeden, 7/2007 - M153-54