

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec Cor for 3 & 4; 33 & 34, T26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 11 Page 4594)

Set post, cor. secs. 33, 34, 3 and 4, from which
A B.Oak 10" dia., bears N.89¼°E., 191 lks. dist.
A B.Oak 20" dia., bears S.45°E., 135 lks. dist.
A B.Oak 12" dia., bears S.65°W., 105 lks. dist.
A W.Oak 12" dia., bears N.47°W., 80 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-73

Found - W. Oak now 18", dead but standing, N.47°W., 52.8 ft. Upper scar had been previously opened & face entirely rotted away. Chopped open lower scar & found good scribe "BT".

No trace found of any other BTs. Corner is in badly burned area.

Set Brass cap at cor. mkd: County Surveyors S33|S34 T26S R7W
Office, 1960 S 4|S 3 T27S R7W

New BTs - 9" W.Oak N.37½°E., 129.5 ft. mkd. T26S R7W S34 CSBT.
No other live trees available in vicinity of corner.
A fence corner, fences E & N bears S.64½°W., 18 ft.

Doug. County Surveyors Office - Milo Godfrey and crew. Nov. 17, 1964 - C.S. File 52/87-98

Found - 18" dead, W.Oak, old BT, N.47°W., 52.8 ft.
9" W.Oak N.37½°E., 129.5 ft., scars very plain.
1960 BT.

3-way fence corner S.64½°W., 18 ft., fences E-W & N.
Brass cap, which had been taken out & thrown in to the brush.

Set Brass cap at cor. mkd: County Surveyors T26S S33|S34 R7W
Office, 1964 T27S S 4|S 3

Set both caps at cor., old cap buried.

New BT - 4" Madrone S.48½°E., 86.1 ft. mkd. S3 CS BT.

Fd. and Use, Cadastral Survey by Peterson, etal. Group #'s 744 and 838. May 1971-74 (DCSO records Vol. 37 Pg. 15168)

Fd. Ok by Mark Heimburger - 10/1998 - M 130-72
Found OK by G. Lang, Oct. 2004 - M145-80 A & B

Fd. 2 BCs, 2 BTs & 3 Way fence corner now 4.0 ft. South of 1964 BC by C. Sweeden, 6/2008 - M156-58