TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 407100

PRIMARY CORNER DESCRIPTION Angle Point for Secs. 3 & 4, T28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5230)

Set post, cor. of secs. 3 and 4, from which
A Laurel 24" dia., bears S.32°E., 42 lks. dist.
An Oak 24" dia., bears S.56°W., 55 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Page 5842)

Intersect the cor. established by Hathorn as the standard cor. of secs. 3 and 4, located by the record bearing & distance from the stump of the SW BT. The marks are obliterated by decay, but evidence of the blazes are still distinguishable.
At the exact cor. point
Set an Iron post 3 ft. long 1 in. dia., 28" in the ground, for angle point, with brass cap marked: A P
1924
from which (new bearing trees)
A Fir 22" dia.,bears N.60°E., 53 lks. dist., marked A P BT.
A Fir 8" dia.,bears N.76°W., 23 lks. dist., mkd. AP BT.
Stump of orig. SW BT, an Oak 28" dia., bears S.56°W., 55 lks.
The orig. SE BT, a Laurel, is rotted out, stump hole bears S.32°E., 42 lks.

Doug. County Surveyors Office - James Byron,Deputy - Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79

Renew Angle point, S.34°53'W., 74.6 ft. from Standard cor. secs. 3 and 4.
Found - Brass cap and NE BT.
New BTs -11" R.Fir bears N.85°E., 29.2 ft. scribed AP CS BT.
15" R.Fir beas S.72°W., 56.7 ft. scribed AP CS BT.