

PRIMARY CORNER DESCRIPTION So. ¼ Cor. for Sec. 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5224)</p> <p>-----</p> <p>Set ¼ sec. cor. from which</p> <ul style="list-style-type: none">A B.Oak 12" dia., bears S.85½°W., 830 lks. dist.A W.Oak 18" dia., bears N.88½°W., 894 lks. dist.
<p>GLO survey by Fred Mensch, under Contract #109 dated 1924 (DCSO records, Vol. 14 Page 5841)</p> <p>-----</p> <p>Proportionate distance.</p> <p>Set an Iron post, 3 ft. long, 1" dia., 10" below the surface of the ground, in cultivated orchard, for cor., with brass cap marked:</p> <p style="text-align: center;"><u>¼ S34</u> 1924</p> <p>The two east trees of the north row of trees of the orchard are used as bearing objects, as follows:</p> <ul style="list-style-type: none">The East tree of the North row, a Walnut, 8" dia., bears N.63°E., 41 lks. dist., not marked.The next tree west in the same row, a Walnut 8" dia., bears N.71°W., 59 lks. dist., not marked. <p>The Ford standard ¼ sec. cor. of sec. 3 re-established, bears N.83°56'E., 7.29 chains.</p> <p>The cor. established by Ford for the ¼ sec. cor. of sec. 34, re-established as angle point, bears N.15°W., 76 lks.</p>
<p>Carl Sweeden - For: Jerald & Barbara Nielsen - March 2002 - Partition Plat 2003-0025</p> <p>-----</p> <p>Found - 2½" BC dn 15" below grd surface in good condition & no BTs remain, established accessories:</p> <p>Set - 5/8"x30" Iron rod w/red plastic cap "SWEEDEN LS 2752" set as follows:</p> <ul style="list-style-type: none">#1. N.07°04'52"E., 343.96', 0.20' SO. of steel "T" post w/BT tag attached, up 0.30'#2. N.34°37'27"W., 417.65', 0.20' SO. of steel "T" post w/BT tag attached, up 0.30'#3. S.45°24'26"W., 135.08', 0.20' SO. of steel "T" post w/BT tag attached, up 0.30'#4. S.46°36'48"E., 243.81', 0.50 NO. of wood post at E/W/S corner, BT tag attached up 0.30'