

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5248)

Set ¼ Sec. post, from which
 A B.Oak, 18" dia., bears N.77°W., 74 lks.
 A B.Oak, 12" dia., bears S.72°E., 93 lks.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - K. Reed, K. Mosley, crew - April 23, 1980 (Added 5/20/2020) - C.S. File 61/6-35

Reported as not found
Original post not found.
Found - Unrecorded 6" dia., W.Oak blazed on four sides is 4 ft South of a wire E-W fence. A check of the ridge call to the west indicates the position of this point is reasonably close enough to center our search radius.
No accessories found. We are unable to locate either of the old BTs.
No new monument or accessories.
Note - There has been some logging in the area. Most recent logging is to the SW.

BLM dependent resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO records Vol. 50 Page(s) 19139-40)

The ¼ sec. cor. of secs. 27 and 34, determined at the corner of wire fences, extending E., W., and S. This position is harmoniously related to other corners of the original survey, as determined from informational retracements, and with local use lines.

At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 S R 7 W

¼ $\frac{S\ 27}{S\ 34}$
1990

from which
 A D.Fir, 22" dia., bears S.32°E., 9 lks. mkd. ¼ S34 BT.
 A D.Fir, 15" dia., bears N.65°W., 32 lks. mkd. ¼ S27 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Found OK by C. Sweeden, Mar. 2003 - 2003-0025