

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5243)

Set 1/4 sec. post, built stone mound, as the post could not be driven deep, from which

A B.Oak 9" dia., bears S.30°W., 118 lks. dist.

A B.Oak 12" dia., bears S.45°E., 52 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - Nov. 1960 - C.S. File 49/79-56

Found - Orig. 12" now 18", down & mostly rotted Oak, S.45°E., 34.3 ft. We find good reverse scribing on old face, "BT".

Mound of stone at corner.

Orig. SW BT gone.

Set Brass cap in mound of stone mkd: County Surveyors Office
1/4 S22 | S23 T27S R7W 1960

New BTs - 18" Pine bears N.44°E., 46.0 ft. scribed 1/4 S23 CSBT

6" W.Oak bears N.83°W., 42.0 ft. scribed 1/4 S22 CSBT

Doug. County Surveyors Office - Stephen Flause; Shawn Means; Karen Reed - March 26, 1980 - C.S. File 61/6-16

Found - 1960 DCSO cap properly stamped, lying next to a N-S fence.

No original BTs found.

A 6" W.Oak now 7" bears N.83°W., 42.0 ft. with a well healed double blaze.

An 18" P.Pine now 21" bears N.44°E., 46.0 ft. with well healed double blaze.

Reset monument at record bearing and distances from bearing trees per Byron, 1966. Stamped "Reset 1980" on cap. Placed a mound of stone around cap. Cap is 1 ft. east of a N-S fence.

New BTs - 14" Madrone (dia. measured at trunk below double trunk) bark scribed "1/4 S23 CS BT" bears S.41°E., 45.6 ft.

A 5" trunk of a Madrone having double trunks, (this trunk being the most northerly) barked scribed "1/4 S22 CS BT" bears S.46°W., 61.5 ft. (bearing taken to center of base)