

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 5244)

Set post, cor. secs. 10, 11, 14 and 15, from which
An Oak 24" dia., bears S.18°E., 291 lks. dist.
A Fir 18" dia., bears S.7°W., 558 lks. dist.
An Ash 12" dia., bears N.63°E., 550 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy
Milo Godfrey; Clete Putnam - Aug. 19, 1960 - C.S. File
52/41 and M 19-42

Found - Orig. 24" now 36" Oak stump. I open & find good
reverse scribing "BT", S.18°E., 192.1 ft.
Orig. 12" Ash, now 30" shows old axe marks. Center
rotted, checks record dist. & brg., recorded
N.63°E., I find should be N.61°E.

Orig. SW BT not found.
Set Brass cap at cor. mkd: County Surveyors Office, 1960

S 10	S 11
S 15	S 14

 T27S R7W

New BTs - 8" W.Oak bears N.86°E., 179.0 ft. scribed S11
T27S R7W CS BT.
12" W.Oak bears S.46½°E., 147.6 ft. scribed S14
T27S R7W CS BT.
8" R.Fir bears S.2½°W., 299.5 ft. scribed S15
T27S R7W CS BT.

No trees near to NW.

Doug. County Surveyors Office - Rod Kimberling, Deputy -
Peter Earle; Mike Cline - Sept. 1, 1977 - C.S. File 59/40-2

Found - 1960 DCSO brass cap.
Orig. 36" dia. Oak, bears S.22°E., 192.1 ft. (Rec.
S.18°E.). This Oak stump has opened blaze, no
visible scribing.
Orig. 22" Ash with rotted out blaze bears N.61°E.,
362.0 ft. (Rec. N.63°E., 363.0 ft.
8" now 10" dia., W.Oak, bears N.88°E., (Rec. N.86°E)
179.0 ft. with well healed single blaze.
12" now 15" dia., W.Oak bears S.45°E., 148.3 ft.
(Rec. S.46½°E., 147.6 ft.) with well healed
single blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

8" now 13" dia., Fir stump bears S.3½°W., (Record S.2½°W.) 299.5 ft. with possible bottom of blaze showing.
Reset Brass cap described by Byron with "RESET 1977" stamped above 1960, 1.0 ft. below ground.
New BTs - An 8" dia., Ash bears S.31½°W., 350.3 ft. double blazed and scribed "T27S R7W S15 CS BT".
New Bearing Object:
A 5/8" x 30" rebar with alum. cap stamped "BO 1" bears N.24½°E., 136.0 ft. in fence line, N.70°W., 148.5 ft. from fence corner.
Set survey marker sign on steel fence post 1.0 ft. south of brass cap. Found 3" x 6 ft. wooden post 2.0 ft. east of brass cap, painted orange and white.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/2/2009 - C.S. File 67/28-11

Found - Brass cap/Iron pipe 1 ft. under ground in open pasture unable to visually see BC/IP as ground saturated with water, felt top of BC/IP. Fence post alongside removed at owner's request. 1960
12" now double trunked W.Oak with a fully healed single blaze on 16" dia., northerly trunk bears N.46½°E., 147.6 (agrees w/1960 rec.) 1960 BT
8" now 16" W.Oak with a fully healed single blaze bears N.86°E., 179.0 (agrees w/1960 rec.) 1960
5/8" I.R. fd., 2" below ground without a cap is found 6' northerly of new fence line bears N.23½°E. 136.0 ft (rec. N.24½°E. 136.0 ft) 1970
New - 20" dia., D.Fir single blazed & scribed "T27S R7W S14 CS BT" bears S.25°E., 145.0 ft.
Note - Fence corner bears N.70°E., 204 ft.
Compass decl. 16½°E.