

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec cor for 3 & 2; 34 & 35 of T26-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 11 Page 4593)

-----  
Set post, cor. sec. 34, 35, 2 and 3, from which  
A B.Oak 18" dia., bears S.87½°E., 127 lks. dist.  
A B.Oak 24" dia., bears N.85°E., 96 lks. dist.  
A B.Oak 24" dia., bears S.78°W., 7 lks. dist.  
A W. Oak 9" dia., bears N.88°W., 38 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-77

-----  
Found - Orig. 24" now 40" B.Oak S.78°W., 4.6 ft. shows old scars, face rotted.  
Orig. 9" now 14" W.Oak N.88°E., 25.1 ft. We open & find good scribing "S".  
Orig. 24" now stump hole, that checks bearing and dist. for SE BT.  
Orig. 24" B.Oak now base of Oak stump, checks bearing and distance for orig. NE BT.

Set Brass cap at cor. mkd: County Surveyors T26-7W  
Office, 1960 

S34		S35
S 3		S 2
T27-7W		

New BTs - 17" R.Fir bears S.26°W., 8.0 ft. scribed S3 T27S  
R7W CS BT.  
7" W.Oak bears S.81°E., 54.8 ft. scribed S2 T27S  
R7W CS BT.  
7" W.Oak bears N.75°E., 46.7 ft. scribed S35 T26S  
R7W CS BT.  
10" double R.Fir bears N.50½°W., 20.0 ft. scribed  
S34 T26S R7W CS BT.

Fd. Ok by M.Farr, 11/96, 1997-0015 & 1997-0016  
Fd. OK by M. Heimbürger, Dec. 1999 - M133-72

DCSO-GIS Corner visitation - 4/6/2006 - Typed: 1/28/2011 - C.S. File 67/33-1

-----  
Monument - 2½" IP w/BC  
Comment - ok

Fd. BC by N. Hibbs, 4/2008 - M156-20  
Fd. BC & 2 BTs by C. Sweeden, 6/2008 - M156-58