TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5246)

Set ¼ sec. post, from which
A B.Oak 20" dia., bears S.85½°W., 992 lks. dist.
A B.Oak 12" dia., bears N.71°W., 1043 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy
Milo Godfrey; Clete Putnam - Dec.1960 - C.S. File 49/79-74

Found - Orig. 12" now 20" B.Oak N.71°W., 688.4 ft. I open & find good scribing "S".
Orig. 20" now 44" B.Oak S.85½°W., 554.7 ft., shows good scar. I do not open.
Set Brass cap at cor. mkd: County Surveyor's Office, 1960 ¼ S 2 / S11
New BTs - 7" Pine bears N.34°E., 177.8 ft. scribed ¼ S2 CS BT.
7" Pine bears S.55°W., 123.8 ft. scribed ¼ S11 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/25/1999 - C.S. File 66/8-5

Found: 2½" brass cap on a 1½" O.D. iron pipe, found knocked over and bent. 1960
COUNTY SURVEYORS OFFICE
T27S R7W
¼ S 2 / S 11
196

Note - Top of brass cap scuffed
Bearings & distances taken from plumb position of IP.
No OBTs found.
7" now 24" dia. P.Pine with a fully healed single blaze, bears N.34°E., 177.8 ft. 1960
7" now 20" dia. P.Pine with a fully healed single blaze, bears S.55°W., 123.8 ft. 1960

Set - Monument straightened, set 1" below ground.
1 3/8" X 5/16" iron bar protrudes 18" above ground bears N.53 3/4°E., 138.4 ft. I.B. is 2 ft. south of a fence corner int. with fences running N-S & E.
27" dia. cedar single blazed low and scribed "1/4 S11 CS BT" bears S33°E, 114.6 ft.