

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5235-36)

Set post, cor. secs. 23, 24, 25 and 26, from which
A W.Oak 12" dia., bears S.75°W., 92 lks. dist.
A B.Oak 12" dia., bears N.13°W., 107 lks. dist.
A B.Oak 20" dia., bears N.72°E., 153 lks. dist.
A B.Oak 12" dia., bears S.75°E., 124 lks. dist.

J.W. Cole Co. Surveyor - Wit. G.W. Finley; Harry Brown
Dec. 30, 1922 - Volume 3 Pg. 133; C.S. File 4/39 and
"old" Corner Book, Page 97

I renewed this corner from three original BTs which check for distance and direction. The hole where the fourth tree stood is visible also checking for direction & distance. I set a ¼ x 30" Iron rod, also 4 x 4 x 40" Oak Post for corner.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; Clete Putnam -Dec. 1, 1960 - C.S. file 49/79-63

Found - Original 12" now 26" Oak, S.75°E., 81.8 ft. We open & find good scribing "S".
Stump hole that checks for original NE BT.
Find 3/8" I.Rod with Y strap on top at corner.
Set Brass cap at cor. mkd. County Surveyors S23|S24 T27S R7W
Office, 1960 S26|S25
New BTs - 9" B.Oak bears N.40°E., 22.4 ft. scribed S24
T27S R7W CS BT.
15" B.Oak bears S.6°E., 34.2 ft. scribed S25 T27S
R7W CS BT.
6" B.Oak bears S.58°W., 9.0 ft. scribed S26
T27S R7W CS BT.
No trees near to NW.

Fd. by Douglas Co. Surveyors Office - Randall W. Smith -
Stephen J. Flaue - 5/12/1998 - C.S. File 66/2-28