

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5236)

Set 1/4 sec. post, from which
 A B.Oak 10" dia., bears N.25°E., 14 lks. dist.
 A B.Oak 6" dia., bears S.60°W., 19 lks. dist.

F.J. Cole/J.W. Cole - Wit. M.A. Cozad; J.H. Criteser; J.S. Wilson; W.A.Taylor - Field Book 66 Pg. 16; Vol. 3 Pg. 179 & "old" corner book, Pg. 96.

Find two trees corresponding to original witness trees to-wit:
 A B.Oak 10" dia., bears N.25°E., 14 lks. Tree is badly chopped, no marks visible.
 A B.Oak 6" dia., bears S.60°E., 19 lks. (Rec. S.60°W) No marks visible.
Mark trees S.60°E 19 lks. and N.25°E., 64 lks.
Set Iron pin 1/2" x 30".

Doug. County Surveyors Office - James W Byron, Deputy Milo Godfrey; Clete Putnam - Dec. 1, 1960 - C.S. File 49/79-65

Found - Iron rod set by Cole.
 16" B.Oak N25°E., 42.2 ft., cut open & find good scribe "BT".
 17" B.Oak S.60°W., (instead of S.60°E. as recorded by Cole) 12.5 ft., showing good scars. Did not open this tree.
Set Brass cap at cor. mkd: County Surveyors Office, 1960
 T27S R7W 1/4 S23|S24
Set alongside Cole's rod.
New BTs - 7" W.Oak N.84°E., 17.6 ft. mkd: 1/4 S24 CS BT.
 Found remnants of rotted Oak showing old axe marks N.25°E., 9 ft.
Corner falls in fence corner, fences N-S & W from corner.