

PRIMARY CORNER DESCRIPTION Center ¼ Cor. for Sec. 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

F.J. Cole, Deputy Co. Surveyor - July 1914 - Vol. 2 Page 179;
Field Book 39 Pg. 47

Set by intersections of quarter lines run through the section
both ways and witnessed by:

36" W.Oak N.68½°W., 268 lks.

6" W.Oak N.41°20'E., 50 lks.

This corner set from original bearing trees.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 11/5/2002 - C.S. File 66/48-2

Found - 1914 36" now 38" dia., 1½ ft. high Oak stump with
axe marks (rec. N.68½°W., 176.9 ft.)

No other BTs fd. Tie made to DLC corner Int. L DLC
48 measured N.74°W., 317.0 ft. from Oak stump.
(See FB 39 Pg. 50 & 51)

Compass decl. 17½°E.

Set - 5/8"x30" iron rod with DCSO alum. cap stamped "C¼
S24 2002" protrudes 7" out of ground at rec.
from center of 1914 BT.

Corner is 1½ ft. East of Westerly R/W fence & 22 ft.
N'ly from West fence line intersection with
Westerly R/W fence.

6" Pine double blazed & scribed "C¼ S24 CS BT" bears
S.69°W., 23.2 ft.

5" dia., D.Fir double blazed & scribed "C¼ S24 CS
BT" bears N.46°W., 34.7 ft.

DCSO brass cap iron pipe Int. L DLC 48 bears
S.81°E., 142.1 ft.

5/8" C R/W pin bears S.23¾°W., 78.0 ft.