

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 5237)

-----  
Set 1/4 sec. post, from which  
    An Oak 15" dia., bears S.80°E., 578 lks. dist.  
    An Oak 12" dia., bears N.87°E., 601 lks. dist.

F.J. Cole, For: Seeley; Taylor; Criteser; Wilson - July 1914 - Field Book 39 Pg. 47; Vol. 2 Pg. 179 and "old" corner book, Page 96

-----  
Renew corner and set post, from which  
    An Oak 15" dia., bears S.80°E., 578 lks.  
    An Oak 12" dia., bears N.87°E., 601 lks.

Doug. County Surveyors Office - James Byron, Deputy Milo Godfrey; Clete Putnam - Dec. 1, 1960 - C.S. File 49/79-64

-----  
Found - Orig. 12" now 20" Oak stump N.87°E., 396.7 ft., center rotted but shows good reverse scribing "BT".  
    Large Oak, down in creek, that checks close for orig. SE BT.  
Set Brass cap at cor. mkd: County Surveyor's 1/4  $\frac{S13}{S24}$  T27S R7W  
Office 1960  
New BTs - 6" W.Oak bears N.36°W., 308.2 ft. scribed 1/4 S13 CS BT.  
    24" W.Oak bears S.89½°E., 381.2 ft. scribed 1/4 S24 CS BT.

Doug. County Surveyors Office - Gregory Quibell, Deputy Danna Ingram; Debbie Stewart - Oct. 16, 1976 - C.S. file 57/36-17

-----  
Found - 1960 Brass cap, properly marked.  
    6" now 9" W.Oak which bears N.36°W., 308.2 ft., alive & well healed blaze.  
    24" now 30" W.Oak which bears S.89½°E., 381.2 ft., alive with well healed blazes.  
I reset brass cap in a 4" x 36" bell tile, 12" below surface of ground and stamp "1975" on cap.  
(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set two brass caps in bell tiles flush with ground along fence south of the corner point.

R.M. 1 bears S.23°E., 162.32 ft. and is stamped:

COUNTY SURVEYORS OFFICE R.M. 1  
1975 1/4  $\frac{S\ 13}{S\ 24}$  T 27 S  
R 7 W

R.M. 2 bears S.51½°W., 228.80 ft. and is stamped:

COUNTY SURVEYORS OFFICE R.M. 2  
1975 1/4  $\frac{S\ 13}{S\ 24}$  T 27 S  
R 7 W

Compass dec. is 20° East.

Found OK by N. Hibbs, Dec. 2005 - 2005-0103 A&B