

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. For 25 & 36; 30 & 31, T.27-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Vol. 12 Pg. 5151)

-----  
Set post cor. to Secs. 25, 30, 31 and 36. Drove charred  
stake and raised mound with trench and pits, as per  
instructions.

Roger Gee, For: E. G. Ziegler Oct. 1967, M 33-48

-----  
Set - 1 1/4" Iron rod by proportionate measurement.  
Note - Wit. Corners Set North of this I. Rod.

Found I.P. August 1990, M 110-59

Doug. County Surveyors Office - Randall Smith, Stephen Flause  
June 8, 1993 - C.S. File 64/43-28

-----  
Found - 1 1/4" dia. iron rebar 2" below ground. (Set in M33-48)  
Rebar measures 32" long. Corner lies in a  
field, owner requests removal of rebar as he  
will plow field deep in near future.

Accessories Found - (bearings based on M33-48)  
3/4" I.R. bears N.0°08'01"W., 226.90 ft. Witness  
corner per M33-48.  
3/4" I.R. bears N.0°08'01"W., 286.35 ft. Witness  
corner per M33-48.  
5/8" I.R. bears N.41°07'07"E., 294.31 ft. (rec.  
N.41°40'08"E., 294.31 ft.) (M110-59)

Set - Witness Cor. 3/4" I.R. bearing N.0°08'01"W., 226.9  
ft. from section corner is referenced and  
removed, I.R. measured 28" long.

A 2 3/8" dia. brass cap on a 1 1/4" O.D. dia. x 32"  
long iron pipe is set at referenced position,  
BC/IP protrudes 1" above ground.

Brass Cap marked:

DOUGLAS COUNTY SURVEYORS

T.27 S

WC

R	S 25	S 30	R
7	S 36	S 31	6
W			W

South 226.9 ft.

1993

OFFICE

Continued on next page.

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31 T.27-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

3/4" I.R. is set along north edge of BC/IP, flush with ground.	
New Accessories - (from BC/IP Witness Cor.)	
5/8" I.R. bears	S.88°28'25"E., 194.15 ft.
5/8" I.R. bears	S.89°55'16"W., 205.85 ft.
5/8" I.R. bears	S.89°58'14"W., 224.66 ft.
5/8" I.R. bears	N.72°41'46"W., 234.39 ft.
5/8" I.R. bears	N.0°24'40"W., 67.32 ft.
3/4" I.R. bears	N.0°08'01"W., 59.45 ft.
W.C. found OK by D. Edwards, Jan. 1998 - 1998-0010	
DCSO-GIS Corner visitation - 7/19/2004 - Typed: 1/28/2011 - C.S. File 67/33-1	
Monument -	BC/IP 1.25"
Comment -	OK