

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19, 30 of T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Vol. 12 Pg. 5152)

Set post cor. to Secs. 19, 24, 25 and 30, from which
A Y.Oak, 8" dia. bears S.16°E., 89 lks. dist.
A Y.Oak, 24" dia. bears S.40°W., 120 lks. dist.
A Y.Oak, 28" dia. bears N.71½°E., 100 lks. dist.
A Y.Oak, 22" dia. bears N.46½°W., 76 lks. dist.

James W. Byron, Deputy County Surveyor; Milo Godfrey; Clete Putnam; December, 1960 - C.S. File 49/79-66

Found - B.Oak, now 25" S.16°E., 58.7 ft. Cut open & find good reverse scribing "R" & portions of others.
W.Oak, instead of B.Oak, now 35", N.46½°W., 50.2 ft.
This tree had been opened previously and was hollow.
Rotted remnants of N.E. and S.W. BTs. Too far gone to find any trace of scribing.
Set - Brass cap mkd: County Surveyor's

S24	S 19	T27S
R7W	S25	S 30 R6W

New Bts - 16" B.Oak S.56½°W., 64.8 ft. mkd. T27S R7W S25 CSBT
11" B.Oak N.24°W., 62.3 ft. mkd: T27S R7W S24 CS BT.
14" W.Oak N.39°E., 65.6 ft. mkd. T27S R6W S19 CS BT.
15" W.Oak S.51°E., 79.7 ft. mkd. T27S R6W S30 CS BT.
This corner is in fence corner with fences E. W. & N. from corner.

Doug. County Surveyors Office - Randall Smith, Stephen Flauser
May 5, 1993 - C.S. File 64/43-30

Found - 2½" dia. DCSO Brass cap on a 1½" O.D. iron pipe, protruding 18" above ground.
22" now 39" dia. W.Oak with a healed blaze, bears N.46½°W., 51.0 ft. (rec. N.46½°W., 50.2 ft.)
Orig. BT.
No other original BT's found.
16" now 23" dia. B.Oak with a fully healed double blaze bears S.56½°W., 64.8 ft.
11" now 13" dia. B.Oak with a fully healed double blaze bears N.24°W., 62.3 ft.

Continued on next page.

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19, 30 of T27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

	14" now 16" dia. W.Oak with a fully healed double blaze bears N.39°E., 65.6 ft.
	15" now 22" dia. W.Oak with a fully healed double blaze bears S.49°E., 79.7 ft. (rec. S51°E., 79.7 ft)
Set -	Surrounded BC/IP with a 24" dia. 12" high mound of stone.
DCS0-GIS Corner visitation - 8/4/2004 - Typed: 1/28/2011 - C.S. File 67/33-1	

Monument -	BC/IP 1.25"
Comment -	ok