

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. 13 & 24; & 18, 19 of T27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Vol. 12 Pg. 5152)

Set post cor. to Secs. 13, 18, 19 and 24, from which
A Y.Oak, 14" dia. bears S.71°E., 63 lks. dist.
A Y.Oak, 16" dia. bears S.35°W., 95 lks. dist.
A Y.Oak, 17" dia. bears N.10¾°W., 134 lks. dist.
A Y.Oak, 15" dia. bears N.16°E., 130. lks. dist.

James W. Byron, Milo Godfrey, Clete Putnam - Nov. 31, 1960
C.S. File 49/79-62

Found - Orig. 17" now 26" down Oak, N.10¾°W., 88.4 ft. We
open & find good reverse scribing "S13".
Find now 24" Oak, face down, that checks bearing &
distance for orig. S.W. BT.
No other BTs found.
Note - Section corner falls in cattle guard. I SET Witness
Corner 5 feet West.
Set - Brass cap at Wit. Cor. mkd: County Surveyor's Office
1960 mkd. W.C. 5 ft East to R7W S13|S18 R6W
S24|S19 T27S
New BTs - 7" W.Oak bears N.23°W., 40.9 ft. scribed WC S13 T27S
R7W BT.
18" R.Fir bears S.62°W., 46.5 ft. scribed WC S24
T27S R7W CS BT.
11" W.Oak bears S.48½°E., 62.3 ft. scribed WC S19
T27S R6W CS BT.
11" W.Oak bears N.4½°E., 32.3 ft. scribed WC S18
T27S R6W CS BT.

(See Also Old Field Book 66 Page 26)

Doug. County Surveyors Office - Randall Smith, Deputy - S.J.
Flause - May 4, 1993 - C.S. File 64/43-13

Found - 1960 2½" dia. brass cap on a 1½" O.D. I.Pipe, pro-
truding 12" above ground.
No original BTs found.
7" now 11" dia. W.Oak with a fully healed double
blaze, bears N.22°W., 40.9 ft. (Rec. N.23°W.,
40.9 ft. 1960 BT.
18" now 18" dia., 4 ft. high D.Fir snag with a
partially healed upper blaze, scribing visible
"W WC S24 CS" lower blaze is healed, bears
S.62°W., 46.5 ft. (agrees w/rec.)

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. 13 & 24; 18 & 19, T27-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

11" now 15" dia. W.Oak with a fully healed double blaze, bears S.47°E., 62.3 ft. (Rec. S.48½°E., 62.3 ft.)
11" now 18" dia. W.Oak with a fully healed double blaze, bears N.6°E., 32.3 ft. (Rec. N.4½°E., 32.3 ft.)
New BT - 11" dia. D.Fir double blazed and scribed "T27S R6W W C S19 CS BT" bears S.55½°E., 50.2 ft.
Cattle Guard noted in 1960 renewal visit now gone. BC/IP lies along west edge of a dirt road.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/11/2001 - C.S. File 66/19-8

Found - 1960 DCSO brass cap, properly mkd., iron pipe along west edge of dirt road, protrudes 8" out of ground.
Note - 3-way fence cor. bears N.84°W., 7 ft.
We renewed this corner in 1993.
1960 NE BT now gone.
1993 SE BT down.
New - 1960 NW & SE BTs fd in good shape, see 1993 renewal
11" dia., W.Oak double blazed & scribed "T27S R7W S13 CS BT" bears N.58½°W., 58.5 ft.
Power pole "2-142" bears N.79½°W., 28.0 ft.
Compass decl. 17 3/4°E.

Fd. Ok by N. Hibbs Jan. 2005 - 2005-0010
Fd. BC & 4 BTs, C Sweeden, M162-68