

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13, 7, 18 of T. 27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Vol. 12 Pg. 5153)

Set post cor. to Secs. 7, 12, 13 and 18, from which
A Y.Oak, 13" dia. bears S.61½°E., 31 lks. dist.
A Y.Oak, 11" dia. bears S.60½°W., 31 lks. dist.
A Y.Oak, 13" dia. bears N.35°W., 45 lks. dist.
A Y.Oak, 9" dia. bears N.10½°E., 51 lks. dist.

James W. Byron, Deputy County Surveyor; Milo Godfrey; Clete Putnam - December, 1960 - C.S. File 49/79-67

Found - Orig. 11" now 20" B.Oak S.60½°W., 20.5 ft. We open & find good scribing "S 1".
Orig. 13" now 18" B.Oak N.35°W., 29.7 ft. shows good scar. I do not open.
No trace of other orig. BTs.
Set - Brass cap at corner mkd: County Surveyor's Office
1960 S12|S 7 T27S
R7W S13|S 18 R6W
New BTs - 20" B.Oak bears S.63°W., 28.1 ft. scribed S13 T27S
R7W CS BT.
20" B.Oak bears S.55°E., 115.3 ft. scribed S18 T27S
R6W CS BT.
20" B.Oak bears N.62°E., 16.3 ft. scribed S7 T27S
R6W CS BT.
18" B.Oak bears N.32°W., 29.7 ft. scribed S12 T27S
R7W CS BT.

Larry E. Monrean, Deputy County Surveyor - Randall Smith
Stephen Flause - March 9, 1984 - C.S. File 62/16-16

Found - I.P. W/B.C. bent over & cut out of position. Mon. was pushed over by recent bulldozer work.
Orig. 11" now 25" dia. B.Oak double blazed with upper blaze opened & rotted out, bears S.63°W. (Rec. S.60½°W) 20.5 ft.
Orig. 13" now 24" dia. B.Oak, rescribed per Byron, well healed double blaze bears N.32°W. (Rec. N.35°W.), 29.7 ft.
20" now 21" dia. B.Oak with well healed double blaze bears S.63°W., 28.1 ft.
20" B.Oak now down & rotted, root hole bears S.55°E. 115.3 ft. (cont. next page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13; 7 & 18, T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

	20" now 25" dia. B.Oak with well healed double blaze bears N.58°E., (Rec. N.62°E. is to root crown of an oak & madrone trees that have grown together; north branch is the Oak BT, south branch is a madrone tree) 16.3 ft.
Set -	I.P. with brass cap was reset using distances of orig. BTs. Cap was stamped "RESET 1984".
Note -	Orig. bearings when intersected did not fit the distances.
New BT -	17" B.Oak, double blazed & scribed "T27S R6W S18 CS BT" bears S.44°E., 130.2 ft.
	See sketch in CS file.
Fd Brass Cap - By Robert Dolan - June 1993 - 1993-0045 A & B Found OK, May 1995 by H.Pieske - 1995-0068 A&B	
DCS0-GIS Corner visitation - 7/19/2004 - Typed: 1/28/2011 - C.S. File 67/33-1	
Monument -	----- 1.25"
Comment -	ok
Fd. BC by M. Farr - 8/2010 - 2010-0033	