

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7 of T27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Vol. 12 Pg. 5153-54)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Y.Oak, 10" dia. bears S.38°E., 29 lks. dist. A Y.Oak, 12" dia. bears S.65½°W., 30 lks. dist.</p>
<p>Frank Cain, July 8, 1910 - "Old" Corner book, Page 98 & FB 55 Page 26</p> <p>-----</p> <p>Reset by running through to sec. cor. A B.Oak 18" dia., N.33°15'W., 23½ lks. A B.Oak 30" dia., S.40°15'E., 20½ lks.</p>
<p>James W. Byron, Deputy County Surveyor - Milo Godfrey; Clete Putnam - December, 1960 - C.S. File 49/79-68</p> <p>-----</p> <p>Found - Scribed Oak stake. B.Oak, now 36", S.40¼°E., 13.5 ft. Chopped scar & found good scribing. A stump hole & a down Oak tree bears N.33¼°W., 15.5' Tree evidently died shortly after being marked & all marks have rotted off.</p> <p>Set - Brass cap at corner alongside scribed stake mkd: County Surveyor's Office 1960 T27S ¼ R7W S12 S 7 R6W.</p> <p>New BTs - 11" I. Cedar N.84°E., 32.1 ft. mkd. ¼ S 7 CS BT. 20" B.Oak N.24°W., 123.3 ft. mkd. ¼ S12 CS BT.</p> <p>Corner falls in fence corner, fences N. S. & E. from corner.</p>
<p>Found B.C. & BTs - June, 1984, R. Ware, M 90-57 Found B.C. May 1995 by H.Pieske - 1995-0068 A&B</p>
<p>FD. ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/28/2002 - C.S. File 66/34-47B</p>
<p> </p>