

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION W.C. Sec. Cor. 1 & 12; & 6 & 7, T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Vol. 12 Pg. 5154)

Section Corner in Creek. Leave Creek, course east.
North, on West Boundary of Sec. 6 - 0.10 chains:
Set - Witness post to Cor. of secs. 1, 6, 7 & 12
from which - An Ash, 6" dia. bears S.63°E., 22 lks. dist.
A Fir, 12" dia. bears S.55¾°W., 87 lks. dist.
A Y.Oak, 11" dia. bears N.11°W., 95 lks. dist.
A Y.oak, 14" dia. bears N.14½°E., 135 lks.

G.G. Stewart, Deputy - For: Julias Sindt - Wit. Chas Kaiser;
V.J. Borsik; Johnson; Littrel; Sirdl; - May 17, 1922
Volume 3 Page 120

Set - 1" iron pipe from one original bearing tree, others
gone. Corner in Creek.
Marked the following trees:
Fir 14" dia. bears N.42°E., 16.8 ft.
Fir 24" dia. bears S.42°E., 97.3 ft.
White Fir 20" dia. S.55¾°W., 57.4 ft. (orig. BT)
Fir, 14" dia. bears N.39°W., 45.4 ft.

James W. Byron, Deputy - Milo Godfrey; S.A. Bilow -
Sept. 9, 1958 - C.S. File 49/62-5

Found - Stewart's 24", now 36" R.Fir, S.42°E., 97.3 ft.
I open & find good scribing "S".
All other BTs gone except NE BT. which is down
has been washed out. Shows good scar. I do
not open.

Note: Corner falls in Creek. I set witness corner 80.0 ft.
South of true corner.

Set - Brass cap at Wit. Cor. mkd.: "Wit. Cor. North 80.0
ft. to $\frac{S\ 1\ |S\ 6}{S12\ |S7}$ T27S

R7W R6W
County Surveyor's Office, 1958
New BTs - 18" R. Fir bears S.78°E., 25.5 ft. scribed W.C.
S7 T27S R6W CS BT.
8" R. Fir bears S.41°W., 25.0 ft. scribed W.C.
S12 T27S R7W CS BT.

Cont. next page:

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION W.C. Sec. Cor. 1 & 12; 6 & 7 of T. 27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" R. Fir bears N.39°W., 63.2 ft. scribed W.C. S1 T27S R7W CS BT. 14" Myrtle bears N.26°E., 14.4 ft. scribed S6 CS BT WC. This tree scribed high above wire fence.
Found OK June, 1984 - R. Ware - M 90 - 57 Found OK May 1995 by H. Pieske - 1995-0068 A&B
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/28/2002 - C.S. File 66/34-43 ----- Found - 1958 DCS0 brass cap iron pipe 4" below ground. 24" now 36" dia., 3 ft. high D.Fir stump previously opened illegible face bears N.82°E., 65.5 ft. (call rec. N.83¼°E., 65.6 ft.) (1922) 18" now 28" dia., 4 ft. high D.Fir stump with a fully healed double blaze, bears S.81½°E., 25.5 ft. (rec. S.78°E., 25.5 ft.) (1958) 8" now 16" dia., D.Fir with a fully healed double blaze, bears S.41°W., 25.0 ft. (1958) 11" now 31" dia., D.Fir with a fully healed single blaze bears N.39°W., 63.2 ft. (1958) No other BTs fd. New - 10" dia., D.Fir double blazed & scribed "T27S R6W S7 WC CS BT" bears N.39°E., 25.0 ft. New N-S fence line 8½ ft. East of corner. Compass decl. 17½°E
2