

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902020

PRIMARY CORNER DESCRIPTION North ¼ cor. Sec. 6, T28-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch, Deputy under Contract #109 dated 1924 (DCSO records, Volume 14 Page 5877)

-----  
Apportioned distance.

Set an Iron post, 3 ft. long, 1" dia., 18" in the ground in mound of stone, for standard ¼ sec. cor. of sec. 6, with brass cap marked:

-----  
SC    ¼    S6  
1924

from which

A W.Oak 10" dia., bears S.47°E., 4 lks. dist. marked  
S C ¼ S6 BT.

A W.Oak 16" dia., bears S.85°W., 23 lks. dist., mkd.  
S C ¼ S6 BT.

(Ford's 1/4 Cor., see Vol. 14 Page 5222)

The cor. established by Hathorn for the standard ¼ sec. cor. of sec. 6, restored as angle point, bears S.34°33'W., 8.97 chs. (See DCSO records, Vol 12 Page 5231)

-----  
H.L. Eppstein, Co. Surveyor - Witn: B.A. Lane; Fitzpatrick Hollis Green - June 1930 - M 1-73; C.S. 14/59; & "old" renewal book Pg. 111

-----  
Standard govt. post ¼ S6 set by Mensch in 1924. Witness trees as follows:

W.Oak 12" dia. bears S.87°45'W., 15.0 ft.

W.Oak 10" dia., bears S.48°30'E., 28.7 ft.

-----  
Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnman - Feb. 1961 - C.S. File 49/79-33

-----  
Found - Brass cap out of ground. Reset from now 24" W.Oak S.85°W., 15.0 ft., shows good scribe.

New BT - 8" R.Fir bears S.18°E., 45.0 ft. scribed N ¼ S6 CS BT.

-----  
Doug. Co. Surveyors Office - Randall W. Smith; Stephen Flause Sept. 13, 1984 - C.S. File 62/21-30

-----  
Found - 1924 GL0 brass cap on a 2" I.P. protrudes 16" above ground, properly marked.

16" now 27" W.Oak with a well healed single blaze bears S.87°W., 15.8 ft. (Rec. S.85°W.,

15.0 ft.) 1924 BLM resurvey.

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902020

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 6 only, T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" W.Oak now a depression in the ground bears  
S.48½°E., 28.7 ft. (Orig., 1924 resurvey)  
8" now a 25" D.Fir with a well healed double blaze  
bears S.20°E., 45.0 ft. (Rec. S.18°E.)  
New Accessory:  
A 5/8" I.Rod with a alum. cap stamped "Douglas Co.  
Rd. BDPA R-W 40" protrudes 4" above ground  
bears N.43°E., 33.8 ft.  
Corner lies in a open field 55.5 ft. south of Reston Rd. #5.

Fd. Ok by D.Edwards, 11/96, M 126-13.

Fd. OK by McLind, surveyed Dec. '96 thru Feb. '98 - M 128-40