

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902030

PRIMARY CORNER DESCRIPTION Angle Point N Bdy Sec 6, T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Ford, Under Contract #44 dated May 30, 1854 (DCSO records, Vol. 12 Pages 5221-22)

Set a post, cor. of secs. 31 and 32, from which
A Red Fir 15" dia., bears N.50°E., 56 lks.dist.
A Laurel 4" dia., bears N.45°W., 5 lks. dist.

GLO survey by Fred Mensch, Under Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5876-77)

Intersect the point for cor. of secs. 31 and 32, established by Ford, located by record bearing and distance from the stump of the original NE. bearing tree, upon which marks are still legible. The NW bearing tree has rotted away. At the exact cor. point, Set an Iron post, 3 ft. long, 1" dia. 28" in the ground, for angle point, with brass cap marked:

AP
1924

from which (new bearing trees)
A Chinquapin, 7" dia., bears S.70°E., 27 lks. dist.,
marke AP BT.
A Fir 24" dia., bears S.7°W., 17 lks. dist., marked
AP BT.

Original NW bearing tree, a Fir stump, bears N.50°E., 56 lks. dist.

The cor. established by Hathorn for the cor. of secs. 31 and 32, bears S.37°42'W., 7.96 chs. dist.

H.L. Eppstein, Co. Surveyor - Wit: B.A. Lane; Fitzpatrick; and Hollis Green - June 1930 - M 1-73; C.S. 14/59 and "old" corner book, Page 111

A.P. set by Mensch in 1925. Standard Gov't post, from which
A Fir 30" dia., bears S.4°30'W., 11.5 ft.
A Chincapin 6" dia., bears S.69°30'E., 18.0 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-32

Renew A.P. N.37°42'E., 525.36 ft. from SE cor. Sec. 31, T27-7
Found - Brass cap and stump of SW BT.
New BTs - 8" Pine S.40½°E., 34.7 ft. scribed AP CS BT.
7" R.Fir N.4°W., 41.0 ft. scribed AP CS BT.

Fd. OK by McLind, surveyed Dec.'96 thru Feb.'98 - M 128-40

continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902030

PRIMARY CORNER DESCRIPTION Angle point N bdy Sec. 6, T28-7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/28/1998 - C.S. File 66/2-43

Found - 2½" dia., brass cap on a 1" O.D. iron pipe,
protrudes 10" above ground, properly marked. 1924
8" now 28" dia., Pine with a fully healed blaze
bears S.40½°E., 34.7'. (Agrees w/rec.) 1961
7" now 18" dia., D.Fir with a fully healed double
blaze, bears N.4°W., 41.0'. (Agrees w/rec.) 1961
15" now 20" dia., 3½' high rotted D.Fir stump with
a previously opened blaze, no scribing visible,
bears N.50°E., 37.0' to blaze. (Agrees w/rec.) OBT
4" now old rotted Madrone with newer sprouts at
record "N.45°W., 3.3 ft." OBT
24" now 28' dia., 1½' high D.Fir stump, no marks
visible, bears S.7°W., 11.2'. (Agrees w/rec as a
blaze distance) 1924
New BTs- 13" dia., B.Oak, double blazed and scribed "AP CS
BT" bears N.52°E., 52.6'.
14" dia., G.Fir, double blazed and scribed "AP CS
BT" bears S.76°W., 15.0'.